



19 in. 2-Post Open Frame Network Rack, 26U

600 mm (23.6 in.) Depth, Flat Pack, Casters and Levelling Feet Included, Black RAL 9005

SKU: 716444 | EAN-13: 0766623716444 | UPC: 766623716444

Open frame rack for 19 inch network and server equipment in an accessible, heavy-duty rack-mount solution - casters included

The 26U 19" 2-Post Open Frame Network Rack from Intellinet Network Solutions is your simple, cost-effective way for housing IT equipment in secure environments that don't require a lockable rack solution. Its open-frame design offers unparalleled accessibility and superior airflow for optimal heat dissipation.

Unrestricted Access

The open frame allows easy access to your equipment from all sides, facilitating effortless installation and maintenance.

Maximum Airflow

The open design ensures efficient heat dissipation, keeping your equipment cool and running smoothly.

Robust Construction

Built with 2 mm (0.08 in.) thick, cold-rolled SPCC steel and finished with a durable powder coating, this rack is engineered for strength and longevity. With a maximum static and dynamic load capacity of 300 kg (660 lbs.), this rack supports even the heaviest of equipment.

Mobility and Stability

Equipped with heavy-duty casters for easy maneuverability or leveling feet for stable installation (both included), it ensures your setup is flexible and secure.

Comprehensive Rackmounting Kit

The packaging includes 20 M6x12 screws, 20 M6 cage nuts, and 20 M6 plastic washers for hassle-free mounting of your devices without additional accessory purchases.

Space-Efficient Shipping

Its flat-packed shipping condition minimizes space requirements and reduces freight costs, making delivery and storage more convenient.

Lifetime Warranty

Enjoy peace of mind with a lifetime warranty, ensuring your investment is protected.

Features:

- Simple and cost-effective solution; great for testing IT equipment and for secure environments that do not require a lockable network cabinet
- Open frame for easy access to equipment from all sides and for maximum airflow with efficient heat dissipation
- Heavy-duty construction with 2 mm (0.08 in.) thick, cold-rolled SPCC steel and powder coating
- Two posts with numbered rackmount space height units
- Maximum static and dynamic load capacity of 300 kg (660 lbs.)
- Four heavy-duty casters (two with brakes) and four adjustable levelling feet included for maneuverability and stability
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm rack-mount equipment
- Includes 19" rackmounting material with 20 M6x12 screws, 20 M6 cage nuts, and 20 M6 plastic washers
- Ships flat-packed to save space and freight costs
- Lifetime warranty

Specifications:

Standards and Certifications

- RoHS
- ANSI/EIA 310-E
- IEC 60297-3

General

- Dimensions (D x W x H): 600 x 600 x 1296 mm (23.62 x 23.62 x 51.02 in.); 26U
- Total height when standing on casters: 1362 mm (53.62 in.)
- Net weight: 21 kg (46.3 lbs.)
- Gross weight: 24.6 kg (54.23 lbs.)
- Maximum static (without casters) and dynamic (with casters) load: 300 kg (660 lbs.)
- Material: powder-coated steel
- Color: black RAL 9005

Package Contents

- 19" 2-Post Open Frame Network Rack, 26U
- 20 x cage nut set for 19" rackmount equipment (M6 screw, M6 cage nut, plastic washer)
- 4 x levelling foot
- 4 x caster
- Assembly material
- Assembly instructions



