



USB-C to DisplayPort Adapter Cable

Converts a DP Alt Mode Signal to a 4K@60Hz DP Output, 1 m (3 ft.), Black

Part No.: [154260](#)

EAN-13: 0766623154260 | UPC: 766623154260

Easily convert a USB-based audio/video signal to DisplayPort

The Manhattan USB-C to DisplayPort Adapter Cable transmits a USB audio/video signal to a DisplayPort projector, flat-panel display, television or similar device. Built-in circuitry allows digital media enthusiasts to easily enjoy USB-based multimedia content on an Ultra High Definition (UHD) display or TV while maintaining simultaneous A/V reception at the source. Its UHD capability supports up to 3840x2160@60Hz and 4K to serve a wide range of resolutions in many devices and UHD applications including training, retail and trade show settings. Your source device must support DP Alt Mode. No additional setup is required. It effortlessly delivers digital content that's stored on a smartphone, tablet, Ultrabook or notebook computer to a display with DisplayPort input capabilities.

Features:

- Easily connects a USB-C device that supports DP Alt Mode to a DisplayPort display, monitor or projector
- Delivers clear, sharp resolution up to 3840x2160@60Hz; supports 4K Ultra HD video aspect ratio of 21:9
- Ideal for connecting a DisplayPort display to a DP Alt Mode-capable smartphone, tablet, Ultrabook, laptop and more

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Compatible only with a USB-C device that supports DP Alt mode; Thunderbolt 3 port compatible
- Slim design makes for a clutter-free desktop; direct-connect cable makes it the perfect travel companion
- Also available in 2 m (6 ft.) length [search part number 152464 at www.manhattanproducts.com]
- Bus powered: no external power supply needed
- Unidirectional design, can only connect from a USB-C source to a DP display
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- FCC
- RoHS2
- USB 3.2
- HDCP
- DP Alt Mode
- DisplayPort 1.2

General

- Supports lane data rates of 5.4 Gbps (HBR2), 2.7 Gbps High Bit Rate (HBR) and 1.62 Gbps Reduce Bit Rate (RBR)
- Resolution: up to 3840x2160@60Hz
- Audio and video output through DisplayPort
- Bus powered: no external power supply
- Supports HDCP pass-through

Connections

- Input: USB 3.2 type-C male
- Output: DP male

Physical

- Adapter cable: 2 m (6 ft.)
- Weight: 0.09 kg (3.2 oz.)

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- DP Alt Mode-supported device

Package Contents

- USB-C to DisplayPort Adapter Cable



