



4-Port Mini KVM Switch

4-Port PS/2

Part No.: 505864

EAN-13: 0766623505864 | UPC: 766623505864

The INTELLINET NETWORK SOLUTIONS KVM Switch is a 4-port mini KVM switch with integrated connection cables. Its PS/2 support on the console side allows you to use a PS/2 keyboard and mouse. It allows you to access, control, boot and reboot four PS/2-enabled computers with only one PS/2 keyboard, mouse and monitor.

Convenient PC Selection

Quickly and easily switch between command formats.

Zero Cabling Hassles for KVM Users

This KVM Switch saves you cabling troubles with its four pair of 1.2 m (4 ft.) KVM connection cables. In fact, you have zero cabling troubles since you don't have to worry about finding suitable cables to fit — they come attached to the KVM switch!

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

Features:

- Operate four PS/2 computers with one keyboard, mouse and monitor
- Simply plug in the attached cables — nothing else required!
- Full keyboard and mouse emulation for error-free booting
- Hotkey commands and LED indicators for computer selection
- No software or power required
- Compatible with all operating systems
- Supports resolutions up to 1920 x 1440 pixels
- Lifetime Warranty

Specifications:

General

- PC connections: 4
- Console connections: 1

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- PC port connectors:
 - 4 x PS/2 (keyboard, mouse)
 - 4 x HD15 male (video)
 - Integrated connection cables: 1.2 m (4 ft.)
- Console port connectors:
 - Keyboard: PS/2
 - Mouse: PS/2
 - Monitor: HD15 female
- Computer selection:
 - Via hotkey
- Video resolution: max. 1920 x 1440
- Video bandwidth: max. 250 MHz
- FCC Class B, CE, RoHS

LEDs

- 1 LED per channel

Environmental

- Plastic housing
- Scan interval: 3 seconds
- Dimensions: 85 (W) x 75 (D) x 26 (H) mm (3.4 x 3 x 1 in.)
- Operating temperature: 0 - 50°C (32 - 122°F)
- Storage temperature: -20 - 60°C (-4 - 140°F)
- Weight: 0.8 kg (1.76 lbs.)

Package Contents

- 4-Port Mini KVM Switch
- Quick install guide

