



## Industrial Gigabit PoE++ Injector

**One 95 W Port, IEEE 802.3bt (4PPoE) Compliant, IP50-Rated Metal Housing, DIN-Rail Mount**

Part No.: **509602**

EAN-13: 0766623509602 | UPC: 766623509602

## Tough Industrial Ethernet Single-Port Gigabit 802.3bt PoE Injector with 95 Watts for an IEEE 802.3bt Powered Device

The Intellinet Network Solutions Industrial Gigabit PoE++ Injector lets you connect your IEEE 802.3bt/af/at-compliant wireless access point, IP phone, network camera and more to a non-PoE LAN switch port so it can supply both a power and a network connection up to 100 meters (328 ft.) away. This 4PPoE injector has an output power rating up to 95 watts, which is enough for even very power-hungry PoE++ devices like motorized PTZ cameras, thin clients, point-of-sale systems, lighting controllers and digital signage applications.

### Designed for harsh industry environments

This Power over Ethernet injector was designed to give you the network connections you need in places that are less than calm or temperate. With its rugged, IP30-rated metal housing, it operates reliably and quietly, even under extreme temperatures that range from -40 to 167°F (-40 to 75°C). In combination with its DIN-rail mounting option and a safe DC power input with plenty of safety features, this injector is ideal for IoT applications in Industry 4.0 and more.

### Reduced wiring costs

There's no need to run AC power lines to get your PD set up and working. Once you've quickly wired DC power to the injector through its three-pin terminal block, simply connect this Ultra PoE Injector to the LAN switch port, and use your existing Cat5/6/6a cabling to deliver power as well as transfer data at

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

10/100/1000 Mbps speeds up to 100 m (328 ft.).

## **Safe protection for your expensive network equipment**

The auto-sensing technology of this PoE Injector ensures that your products are protected from power problems like short circuits (short GND), current overloads and high voltages. Port surge protection up to 6 kV and ESD protection up to 8 kV make its safety complete.

### **Features:**

- Power over Ethernet with output up to 95 watts
- IP50-rated metal housing to withstand harsh industrial conditions
- Suitable for extreme operating temperatures of -40 to 75°C (-40 to 167°F)
- Option for DIN-rail installation
- Ideal for power-hungry IoT devices like motorized IP cameras, thin clients, PoE lighting and more
- Supports 10/100/1000 Mbps data rates
- Distance support: up to 100 m (328 ft.)
- Compatible with IEEE 802.3bt/at/af-compliant powered devices (PD) such as network cameras, wireless access points, VoIP phones and more
- Short-circuit, overload and high-voltage protection
- Auto-sensing PoE awareness to ensure that power is only sent to IEEE 802.3bt/at/af-compliant devices; non-PoE devices only receive data
- Grounding point to protect equipment from external electrical surges
- DC input (48 - 57 V) through terminal block
- ESD protection up to 8 kV (air) and 6 kV (contact)
- Port surge protection up to 6 kV
- Rated for shock (IEC 60068-2-27), freefall (IEC 60068-2-31) and vibration (IEC 60068-2-6)
- Saves time and money by delivering data and power via existing network cables
- LED indicators for power input and PoE output
- Requires additional industrial power supply (not included)
- Fully TAA-compliant
- Three-year warranty

### **Specifications:**

#### **Standards**

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3bt (PoE++/4PPoE Power over Ethernet)
- IEEE 802.3 (10Base-T Ethernet)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000BASE-T Gigabit Ethernet)

#### General

- Media support:
  - 10Base-T Cat5e/6/6a UTP/STP RJ45
  - 100Base-TX Cat5e/6/6a UTP/STP RJ45
  - 1000Base-T Cat5e/6/6a UTP/STP RJ45
- Ports:
  - One RJ45 gigabit data input port
  - One 4-pin terminal block power input port
  - One RJ45 PoE power + gigabit data output port
- Certifications: FCC, CE, RoHS, REACH, UKCA, TAA
- MTBF: 1M hours

#### Electrical

- DC input: 48.0 - 57.0 V DC, up to 2.3 A, 4-pin terminal block
- DC output: 95.0 W, 54.0 V DC, RJ45 PoE port
- Power consumption: 100.0 W (max.)

#### PoE Pinout

- Pin 1: DC (-)
- Pin 2: DC (-)
- Pin 3: DC (+)
- Pin 4: DC (+)
- Pin 5: DC (+)
- Pin 6: DC (+)
- Pin 7: DC (-)
- Pin 8: DC (-)

#### DC input pin assignment

- PWR1 +
- PWR1 -
- PWR2 +
- PWR2 -

#### LED

- PoE, power

#### Physical

- IP50-rated metal housing
- DIN rail: In accordance with IEC/EN 60715 (top hat)
- Dimensions (L x W x H): 58 x 61 x 26 mm (2.28 x 2.4 x 1.02 in.)
- Net weight: 137 g (0.3 lbs.)
- Gross weight: 164 g (0.36 lbs.)
- Operating temperature: -40 - 75°C (-40 - 167°F)
- Storage temperature: -40 - 85°C (-40 - 185°F)

- Operating humidity: 10 - 95% RH, non-condensing
- Storage humidity: 10 - 95% RH, non-condensing
- Recommended AWG for terminal block: 14-22

#### Package Contents

- Industrial Gigabit PoE++ Injector
- Instructions



For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

