



2-Port HDMI USB-C KVM Switch 4K@60Hz with Dual Power Delivery

Two USB-C Host Ports, Two USB-A and One HDMI Output Ports, 100 W Power Delivery, One USB-A Peripheral Port (up to 5 Gbps), Aluminum, Gray

Part No.: [154390](#)

EAN-13: 0766623154390 | UPC: 766623154390

2-Port USB Type-C PD KVM Switch with Single 4K60 HDMI Monitor and 100W Power Delivery Pass-through Ports to Boost Your Productivity

Simplify your workspace with the Manhattan 2-Port HDMI USB-C KVM Switch, designed to let you control two USB-C devices with a single USB-A keyboard, mouse, and HDMI monitor. Whether you're switching between a work laptop and a personal device or managing multiple systems, this KVM switch makes multitasking effortless.

Wide Compatibility for Versatile Use

Compatible with Windows®, macOS®, Android™, iOS®, Chrome OS®, iPadOS®, and Linux®, this KVM switch supports a wide range of devices, including MacBook®, iPad® Pro, iPhone 15/16, Chromebook™, Samsung Galaxy, and more.

Power and Productivity Combined

Charge your devices as you work with USB Power Delivery (PD). The switch delivers up to 85 W to a single laptop or 65 W + 20 W when powering two devices simultaneously. For reliable performance, simply connect a 60 W minimum PD charger (for operation) or up to 100 W for maximum PD output. (PD charger not included)

Crystal-Clear 4K Visuals

Enjoy hi-res image quality with resolutions up to UHD 4K@60Hz (3840 × 2160), ensuring sharp details and vibrant colors - perfect for design work, media playback, or detailed visual tasks.

Convenient Switching and Connectivity

Easily toggle between devices using the top-mounted select button for fast and reliable switching. In addition to the two USB-A ports for mouse and keyboard, there's a third USB-A port with 5 Gbps as hub port providing convenient access for external storage drives, printers, and other USB peripherals.

The Perfect Solution for Hybrid Workspaces and IT Professionals

Ideal for sharing peripherals between work and personal devices or for IT admins managing two systems during maintenance tasks, this 2-Port HDMI USB-C KVM Switch is designed for maximum efficiency and convenience.

Features:

- Controls two USB-C equipped devices from a single USB-A keyboard, mouse, and HDMI monitor
- Switching via top-mount select button
- Charges one laptop with USB Power Delivery (PD) up to 85 W or two laptops with up to 65 W and 20 W
- Resolutions up to Ultra-High-Definition (UHD) 4K@60Hz (3840 × 2160)
- Requires an external PD charger with a minimum of 60 W for operation and 100 W for maximum PD output (PD charger not included)
- Overload and overcurrent protection
- Additional USB 3.2 Gen 1 (formerly USB 3.0) Type-A hub port with 5 Gbps to connect storage drives, printers, scanners and more
- Compatible with any operating system including Windows®, macOS®, Android™, iOS®, Chrome OS®, iPadOS®, and Linux®
- Compatible with USB-C DP-Alt-Mode-supported laptops, tablets, and phones including Apple® MacBook®, iPad® Pro, iPhone 15/16, Chromebook™, Samsung Galaxy, and more
- Ideal for sharing peripherals between personal and work laptops in a home office or for IT admins managing two systems during maintenance tasks
- HDR10 for superior contrast and brilliant colors

- Fully HDCP 2.3 compliant, backward compatible
- Compact desktop format with rugged aluminum housing
- Compatible with USB4[®] and Thunderbolt[™] 3 / 4 interfaces
- Fully TAA-compliant
- Three-year warranty

Specifications:

Standards and Certifications

- DP 1.4 Alt Mode over USB-C
- USB 3.2 Gen 1 (USB 3.0)
- HDMI 2.0
- HDCP 2.3
- CE
- FCC
- RoHS
- REACH
- UKCA

Connections

- Console ports
 - 1 x HDMI 19-pin, female (for monitor)
 - 3 x USB-A 9-pin, female, 5 Gbps (for mouse, keyboard, and peripherals)
- Computer/host ports
 - 2 x USB-C 24-pin, female
- Other
 - 1 x USB-C 16-pin, female (PD input as power supply)
- USB-C PD charging port: 100.0 W input / 85.0 W output max.
- Voltage/current settings (max.):
 - 5.0 V / 3.0 A
 - 9.0 V / 3.0 A
 - 15.0 V / 3.0 A
 - 20.0 V / 5.0 A
- Single USB-C port use: up to 85.0 W output, Dual USB-C port use: up to 65.0 W and 20.0 W output

Protection Characteristics

- Short-circuit (SCP)
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 130% (max)

LEDs

- Source1
- Source2

Physical

- Aluminum housing
- Dimensions (L x W x H): 125 x 70 x 14 mm (4.92 x 2.76 x 0.55 in.)
- Net weight: 135 g (0.3 lbs.)
- Gross weight: 170 g (0.37 lbs.)

Operating Environment

- Operation temperature: 0 - 45°C (32 - 104°F)
- Storage temperature: -10 - 80°C (14 - 140°F)
- Humidity (noncondensing): 5 - 90% RH

System Requirements

- Compatible with any operating system and any device that supports DP Alt mode

Package Contents

- 2-Port HDMI USB-C PD KVM Switch 4K@60Hz
- Instructions

Note:

- Mac computers can only be controlled with a standard PC mouse and keyboard, not with Mac peripherals



