



19" 1U Rackmount 8-Outlet Power Distribution Unit (PDU) with C14 Plug

Eight EU CEE 7/3 Sockets, Built-in 2 m Power Cord with C14 Plug, 10 A, Horizontal Mount, Aluminum, Black/Silver

SKU: 716642 | EAN-13: 0766623716642 | UPC: 766623716642

Reliable Rack-Mounted Power Strip with 8 EU Sockets and Universal C14 Plug for Your Network

Engineered for professional environments, this **19" 1U Rackmount 8-Output PDU** from Intellinet Network Solutions delivers safe and efficient power distribution for network, telecom, security, and AV equipment. Featuring **eight EU CEE 7/3 (Type F) outlets**, it ensures consistent power supply in data centers, server rooms, or control cabinets.

Flexible Power Input with C14 Plug

The built-in **2 m power cord with a universal C14 plug** allows easy connection to any C13 PDU, UPS, or C13 to AC mains cable, offering maximum flexibility across different regions and setups. Designed for seamless integration into standard **19-inch racks**, the PDU supports **horizontal 1U mounting** with front-facing brackets. Its **angled outlet orientation** provides better cable management in tight rack environments, while **contact-shuttered outlets** add an extra layer of safety by limiting direct access to live parts.

Durable and Built for Daily Use

Constructed from **black anodized aluminum**, the PDU is built to last in demanding settings. The **IP20-rated housing** offers protection against solid objects, while a **grounding point** safeguards connected devices from electrical surges.

Features:

- 8-way single-phase PDU with European type F sockets for electrical equipment, ideal for networking, telecom, security and audio/video
- Built-in 2 m power cord with universal C14 plug, compatible with any regional C13 to AC mains cable, C13 PDU or UPS
- Sockets with increased touch protection through contact shutters
- Horizontal 1U 19" rack-mount installation
- Angled outlet orientation for easier cable management in tight rack environments
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm racks
- Durable aluminum construction with IP20-rated housing
- Grounding point to protect equipment from external electrical surges
- Bracket installation style: frontal
- For indoor use only
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- UKCA
- IEC 60884
- IEC 60297
- IP20

Electrical

- AC input: 220.0 - 250.0 V; 50 - 60 Hz
- Operating voltage: 230.0 V
- Plug standard: C14
- Socket/outlet standard: EU CEE 7/3 (Type F); IEC 60884
- Maximum load: 2,500.0 W
- Overload protection: 10.0 A maximum load current

Physical

- Dimensions (L x W x H): 45 x 482.2 x 45 mm
- 1U rack mount
- Cable length: 2 m
- Cable type: H05VV-F 3G 1.5 mm²

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Socket angle: 35°
- Net weight: 800 g
- Gross weight: 900 g
- Housing: aluminum

Package Contents

- 19-inch 1U 8-Way PDU with C14 power cable

