



4K@60Hz DisplayPort Monitor Cable, 1 m

DisplayPort Male to Male, Double Shielding, 1440p@144Hz, PVC Jacket with Latches, Black

Part No.: **356794**

EAN-13: 0766623356794 | UPC: 766623356794

High-definition performance for personal computing

Manhattan DisplayPort Cables provide a single-cable solution that delivers both high-definition digital audio and video signals between desktop and notebook computers and an output device. With 21.6 Gbps bandwidth (HBR2), DeepColor and 24-bit, 8-channel uncompressed audio capability, the 20-pin connector is small, compact and ideal for use with DisplayPort-equipped computers, flat-panel displays, slim-profile devices and many consumer electronics including Blu-ray players and game consoles. Full foil and braided shielding, molded boots with strain relief, protective PVC jackets and gold-plated connections help Manhattan DisplayPort Cables provide maximum conductivity and clear, crisp signal transmissions with reduced EMI interference and distortion.

Features:

- DisplayPort 20-pin male to DisplayPort 20-pin male latching connections
- Connects a PC to a DP-enabled display with resolutions up to 4K@60Hz UHD (3840 × 2160)
- Foil and braid double shielding to reduce EMI and other interference sources
- Supports Multi-Stream Transport (MST) to daisy-chain multiple displays
- Up to 21.6 Gbps bandwidth
- Uncompressed 8-channel audio

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Fully compliant with DisplayPort High Bit Rate 2 (HBR2)
- Molded PVC boot
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- UKCA
- UL 20276
- DisplayPort 1.2

Connectors

- DisplayPort 20-pin male with latches (2)
- Nickel plated contacts
- Molded PVC boot

Cable

- 28 AWG
- Shielding: aluminum and braid
- Withstanding voltage: 300 VDC
- Insulation resistance: 5 MOhm
- Contact resistance: 10 Ohm
- PVC jacket
- Length: 1 m
- Net weight: 69 g
- Gross weight: 96 g

Package Contents

- 4K@60Hz DisplayPort 1.2 Monitor Cable



