



UK Power Cable C13 to BS1363, 1 m

AC Power Cord with C13 to British Mains 3-pin, 10 A, 250 V, For PC, Monitor, Printer and TV, Black

SKU: 355834 | EAN-13: 0766623355834 | UPC: 766623355834

PC Power Cord or Monitor Power Cable 1m - Great as a replacement or spare AC power supply cable for printer, TV, server, and more

The Manhattan UK Power Cable BS1363 to C13, 1 m easily connects and extends the reach between a three-prong power outlet and a personal computer, monitor, printer, power adapter or other compatible piece of equipment. Ideal for new systems or replacement applications, this UL-certified power cable is engineered and built from quality materials that meet current safety approvals to deliver and maintain reliable connections. Fully molded boots with strain relief, a durable PVC jacket, and heavy-duty construction enable this power cable to help provide maximum electrical conductivity to transmit dependable power where and when needed.

Features:

- Connects a device with three-pin C14 inlet to a standard three-slot UK AC or similar power outlet
- Great for powering a PC, monitor, printer, TV, scanner, server and more
- Ideal replacement, upgrade or spare power cable for misplaced or overused ones
- Pure bare copper wire for maximum conductivity
- Flexible, durable PVC jacket with heavy-duty strain relief
- High-temperature resistance for use in areas that are not air conditioned
- For indoor use only
- Lifetime warranty

Specifications:

Standards and Certifications

- UKCA
- CE
- RoHS
- REACH
- IEC 60320
- VDE

General

- One BS1363 male
- One IEC 60320 C13 female
- Maximum current: 10.0 A
- Maximum voltage: 250.0 V AC

Physical

- Wire: 100% pure bare copper (Cu)
- Jacket and boot material: PVC
- Number of cores: 3
- Number of strands / strand thickness: 24 / 0.2 mm
- Insulation thickness: 0.6 mm
- Jacket thickness: 0.8 mm

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Nominal overall diameter: 6.5 mm
- Length: 1 m
- Cable type: H05VV-F 3G 0.75 mm²
- Net weight: 135 g
- Gross weight: 140 g

Environmental

- Operation temperature: -10 - 60°C
- Operating humidity (non-condensing): 10 - 85%
- Storage temperature: -20 - 70°C
- Storage humidity (non-condensing): 5 - 90%

Package Contents

- UK Power Cord BS1363 to C13, 1m



