



19" Basic Wall Mount Network Cabinet, 20U, 560 mm (22 in.) Depth, Gray

Cost-Effective Rack Enclosure, Flat Pack, Free-Standing or Wall-Mount, Optional Casters, Gray RAL 7035

SKU: 716802 | EAN-13: 0766623716802 | UPC: 766623716802

Affordable 19-Inch Network Enclosure, 20U, 560 mm Depth, for Organized and Secure IT Installations

This SOHO/Eco Wall Mount Cabinet from Intellinet Network Solutions delivers an affordable way to organize and protect your essential IT, telecom, server, or AV equipment. Designed for small to medium installations, it offers a secure, dependable housing without unnecessary complexity -making it ideal for offices, IT closets, and utility spaces.

Durable Construction and Reliable Performance

Built from sturdy cold-rolled SPCC steel with an antistatic powder coating, this cabinet provides long-lasting strength and protection. Its robust frame supports a maximum load of 60 kg (132 lbs.). It follows IEC 60297 and EIA-310 standards, ensuring full compatibility with all 19 in. rack-mount equipment.

Flexible Installation for Any Workspace

The cabinet's versatile design accommodates a range of mounting needs. It can be installed directly on a wall to free up valuable floor space or used as a free-standing unit - either stationary or mobile with the addition of optional casters. Pre-punched cable entry openings at the top and bottom simplify setup and keep wiring tidy from the start.

Secure Access and Controlled Airflow

The IP20-rated housing provides basic protection against accidental contact. A reversible, 120° swing tempered-glass front door allows convenient access from the left or right side and features a secure cam lock with two keys for reliable access control. Standardized 120 × 120 mm cutouts in the roof support the installation of cooling fans to maintain proper airflow in more demanding environments.

Smart Features for Everyday Efficiency

Numbered rack units make equipment placement straightforward, while the integrated threaded mounting points on the bottom allow quick attachment of optional casters for added mobility. The cabinet ships flat-packed to reduce both storage requirements and freight costs.

Features:

- Budget-friendly, organized, and secure enclosure for network, server, telecommunications and AV equipment
- Sturdy cold-rolled SPCC steel construction with antistatic powder coating
- Maximum load capacity of 60 kg (132 lbs.) both static and when standing on casters
- Wall-mountable for network areas with limited floor space (wall-mounting hardware not included)
- Usable installation depth: 500 mm (19.7 in.)
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm rack-mount equipment
- IP20-rated housing
- Reversible tempered-glass door that can swing open 120° from the left or right side
- Secure cam lock with two included keys

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Pre-punched cable entry openings on top and bottom
- Ready for mobility with four threaded mounting points for optional casters (available separately, model #716819)
- Standard 120 x 120 mm cutouts in the roof for mounting cooling fans (available separately, model #716154)
- No grounding kit included (available separately, model #712187)
- Numbered rackmount space height units
- Front mounting rails only
- Side panels not removable
- Ships flat-packed to save space and freight costs
- Three-year warranty

Specifications:

Standards and Certifications

- RoHS
- REACH
- IP20 protection rating
- ANSI/EIA 310-E
- IEC 60297-2
- DIN 41494, Part 1+7

General

- External unit dimensions (D x W x H): 400 x 540 x 976 mm (15.75 x 21.26 x 38.43 in.); 20U
- Usable installation depth: 500 mm (19.7 in.)
- Height with optional casters: 1031 mm (40.59 in.)
- Outer diameter wall-mounting holes: 11 mm (0.43 in.)
- Net weight: 23.8 kg (52.47 lbs.)
- Gross weight: 25.4 kg (56 lbs.)
- Maximum load: 60 kg (132 lbs.) static and dynamic
- Material: powder-coated steel
- Steel thickness: 1.5 mm (0.06 in.) on profile rails, up to 1.2 mm (0.05 in.) on other pieces
- Color: gray RAL 7035

Package Contents

- 19 inch Basic Wall Mount Cabinet, 20U, 560 mm (22 in.) Depth, Flat Pack, Gray
- Assembly material
- Assembly instructions
- Two door keys



