



19" 2U Rackmount 12-Outlet PDU with Circuit Breaker

Recessed Power Distribution Unit with 3-Pin AU/NZ Sockets, 10 A, Overload Protection, Built-in 2 m Power Cord with Type I Plug, Horizontal Mount, Aluminium, Black/Silver

SKU: 716857 | EAN-13: 0766623716857 | UPC: 766623716857

19-inch Rack Mount 12-Way PDU with AU / NZ Sockets, Circuit Breaker Protection and Recessed Design

The 19 in. 2U Rackmount 12-Outlet PDU from Intellinet Network Solutions is designed to deliver reliable and efficient power distribution in professional rack environments across Australia and New Zealand. Featuring 12 Type I (AS/NZS 3112) outlets, this single-phase unit is ideal for networking, telecommunications, security systems, and audio/video installations, ensuring dependable power delivery for critical equipment.

Reliable Power Distribution with Safe Protection

Equipped with an integrated single-pole 10 A circuit breaker, this PDU provides effective overload protection to safeguard connected devices. The built-in protection mechanism helps prevent damage caused by excessive current, ensuring stable and secure operation in demanding environments. Additional safety is provided by socket contact shutters, which offer increased touch protection during everyday use. A dedicated grounding point provides protection against external electrical surges, helping to maintain system stability and safeguard connected devices.

Recessed Design Optimised for Front Rack Installation with Extra Clearance

The recessed housing design makes this PDU particularly suitable for front mounting in 19" racks and cabinets. By positioning the outlets slightly behind the mounting plane, it provides extra clearance for plugs and cables, preventing interference with rack doors and allowing for cleaner, more organized cable routing.

Durable Construction for Professional Environments

Constructed from high-quality aluminum with an IP20-rated housing, the unit offers long-lasting durability and protection in professional settings. Compliance with IEC 60297 and EIA 310 standards guarantees compatibility with all standard 19" (482.6 mm) racks, making it a versatile choice for a wide range of installations. The built-in 2-meter power cord with AS/NZS 3112 plug ensures straightforward connection to local power sources, reducing installation complexity and eliminating the need for additional accessories.

Features:

- 12-way single-phase PDU with Australia/New Zealand Type I sockets for electrical equipment, ideal for networking, telecom, security and audio/video
- Integrated single-pole 10 A circuit breaker for reliable overload protection
- Recessed design allows front mounting with 50 mm extra clearance for plugs and cables to prevent interfering with rack door
- Built-in 2 m power cord with AS/NZS 3112 plug
- Horizontal 2U 19-inch rack-mount installation
- Sockets with increased touch protection through contact shutters
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm racks
- Durable aluminum construction with IP20-rated housing
- Grounding point to protect equipment from external electrical surges
- Bracket installation style: frontal
- For indoor use only
- Three-year warranty

Specifications:

Standards and Certifications

- RCM
- AS/NZS 3112
- AS/NZS 62368.1
- IEC 60297
- IP20

Electrical

- AC input: 220.0 - 250.0 V; 50 Hz
- Rated voltage: 230.0 V

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Rated current: 10.0 A
- Plug standard: AS/NZS 3112 (Type I)
- Socket/outlet standard: AS/NZS 3112 (Type I)
- Maximum load: 2,500.0 W
- Circuit breaker: SAA-certified single-pole 10.0 A, resettable

Physical


- Dimensions (L x W x H): 89.2 x 485.9 x 95 mm
- 2U rack mount
- Cable length: 2 m
- Cable type: compliant with AS/NZS 3191 (3-core, 1.5 mm²)
- Net weight: 1.57 kg
- Gross weight: 1.7 kg
- Housing: aluminum
- Recessed design: brackets with 50 mm setback for additional plug and cable clearance

Environmental

- Operating Temperature: 0 to 50 °C
- Storage Temperature: -20 to 60 °C
- Humidity: 0 to 80% RH (non-condensing)

Package Contents

- 19" 2U Rackmount 12-Outlet PDU with Circuit Breaker with 2 m power cable



For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

