



Recessed 19" 1U Rackmount 8-Outlet PDU with Circuit Breaker

EU CEE 7/3 Sockets, 16 A, Overload Protection and On/Off Switch, Built-in 3 m Power Cord with EU CEE 7/7 Plug, Horizontal Mount, Aluminum, Black/Silver

SKU: 716864 | EAN-13: 0766623716864 | UPC: 766623716864

19-inch Rack Mount 8-Way PDU (Power Distribution Unit) with Overload Protection and Recessed Design

Provide reliable power distribution for rack-mounted equipment with this recessed 8-Output 19 in. 1U Rackmount PDU from Intellinet Network Solutions. Designed for professional IT, AV and telecom environments, it delivers dependable power management for networks and audio/video installations. Its robust aluminum housing and horizontal 1U form factor make it an ideal solution for organized and efficient rack integration.

Recessed Design Optimized for Front Rack Installation with Extra Clearance

The recessed housing design makes this PDU particularly suitable for front mounting in 19" racks and cabinets. By positioning the outlets slightly behind the mounting plane, it provides extra clearance for plugs and cables, preventing interference with rack doors and allowing for cleaner, more organized cable routing.

Integrated Circuit Breaker Protection and More Safety Features

An integrated 16 A circuit breaker protects connected equipment from overload conditions and helps ensure reliable operation in demanding environments. The built-in on/off switch offers convenient power control directly at the PDU, while a dedicated grounding point provides additional protection against external electrical surges. Sockets with integrated contact shutters increase touch protection and improve operational safety in professional installations.

European Compatibility

The built-in 3 m power cord features a hybrid EU CEE 7/7 plug that supports both European type F and French type E wall sockets, offering flexible deployment across a wide range of installations. The PDU distributes single-phase power through eight EU CEE 7/3 outlets, making it suitable for standard rack equipment used throughout Europe.

Durable Construction for Data Center and Network Environments

Built with a strong aluminum housing and an IP20-rated enclosure, this rack PDU is engineered for long-term reliability in networking, telecom, surveillance and AV applications. Compliance with IEC 60297 and EIA 310 standards ensures compatibility with all standard 19-inch racks and cabinets, enabling seamless integration into professional infrastructure.

Features:

- 8-way single-phase Power Distribution Unit (PDU) for electrical equipment, ideal for networking, telecom, security and audio/video
- Integrated 16 A circuit breaker for reliable overload protection
- Recessed design allows front mounting with 95 mm extra clearance for plugs and cables to prevent interfering with rack door
- Built-in 3 m power cord with EU CEE 7/7 hybrid plug, fits both European type F and French type E sockets
- Horizontal 1U 19-inch rack-mount installation
- Sockets with increased touch protection through contact shutters
- Angled outlet orientation for easier cable management in tight rack environments
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm racks
- Durable aluminum construction with IP20-rated housing
- Grounding point to protect equipment from external electrical surges
- Bracket installation style: frontal
- For indoor use only
- Three-year warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- IEC 60297
- IEC 60884
- IP20

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Electrical

- AC input: 220.0 - 250.0 V; 50 - 60 Hz
- Rated voltage: 230.0 V
- Plug standard: EU CEE 7/7 (Type E+F); IEC 60884
- Socket/outlet standard: EU CEE 7/3 (Type F); IEC 60884
- Maximum load: 4,000.0 W
- Overload protection: 16.0 A circuit breaker, push-to-reset
- Switch: on/off
- MTBF: >100,000 hours

Physical

- Dimensions (D x W x H): 95 x 482.6 x 44.4 mm
- 1U rack mount
- Cable length: 3 m
- Cable type: H05VV-F 3G 1.5 mm²
- Socket angle: 35°
- Net weight: 900 g
- Gross weight: 1 kg
- Housing: aluminum
- Recessed design: brackets with 95 mm setback for additional plug and cable clearance

Environmental

- Operating Temperature: 0 to 50 °C
- Storage Temperature: -20 to 60 °C
- Humidity: 0 to 80% RH (non-condensing)

Package Contents

- 8-Way PDU, Recessed, 19 inch 1U Rack-Mount, Power Distribution Unit with On/Off Switch and Overload Protection



