



Domotz Pro Box C-1

Unified System for Remote Monitoring and Cloud Management of Networks and IP Devices

SKU: 526425 | EAN-13: 0766623526425 | UPC: 766623526425

The Domotz Pro Box C-1 - your convenient go-to tool for remote network monitoring and management

The Domotz Pro Box from Intellinet Network Solutions monitors and manages your network and devices remotely in real-time via web or app. Deployment is fast and easy with automatic detection of IP devices. The Domotz Pro Box lets you gain cloud access to those devices, manage an unlimited number of clients, apply remote power management for PDU and PoE switches, perform network diagnostics and receive real-time notifications about network issues.

Detailed device and network monitoring

Monitor anything: internal and external IP addresses, across multiple VLANs, and any ports or devices. Device status is checked every 30 seconds and is visible from both mobile and web apps. You can also monitor data traffic for individual network interfaces of SNMP-enabled devices.

Remote cloud access

The Domotz software provides remote connectivity to devices using HTTP, HTTPS, RDP, SSH and Telnet connections. Router settings do not have to be configured; VPNs are not required. It supports remote desktop to conveniently access client machines through an encrypted connection.

Remote power management

Turn devices on and off using the web or mobile apps via PoE (Power over Ethernet), PDUs (Power Distribution Units), smart plugs, and managed network switches. Use the auto Wake-on-Lan feature to wake up devices as soon as they are found to be offline.

Alert settings

Receive event-based mobile push notifications and e-mail alerts. Alerts can be configured on a per-account basis.

Diagnostics

Check your network's performance, analyze its bandwidth, run speed tests and monitor device connectivity to identify possible bottlenecks and packet loss.

Plug-and-play in ~15 minutes

Pre-installed with the Domotz agent. Power it on, plug in Gigabit Ethernet, follow the app onboarding - auto-discovery handles the rest.

Fanless and silent

Passive cooling means no moving parts and no audible noise. Fits behind a display, on a shelf in a closet, or under a desk without anyone noticing.

SNMPv3, Multi-VLAN, enterprise ready

The C-1 supports the full Domotz platform - SNMPv3, Multi-VLAN, enterprise networks, and custom scripts and sensors. No restrictions, no caveats.

Auto-updates, hands-off

Firmware and agent updates apply automatically. No OS babysitting, no patch windows to schedule, no maintenance line item.

Features:

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Monitors and manages your network and devices remotely in real-time via web or app
- Automated network mapping for fast deployment - automatically detects and provides a detailed display of your IP devices
- Plug-and-play installation: just follow the app onboarding and auto-discovery will handle the rest
- Remote-device cloud access to conveniently connect to devices using HTTP, HTTPS, RDP, SSH and Telnet connections
- Multi-client account management - features one user-friendly dashboard to manage an unlimited number of clients
- Remote power management for PDUs and PoE switches - includes port/device power cycling and manual or automatic rebooting
- Network diagnostics and troubleshooting - identifies possible bottlenecks and packet loss
- Configurable network and device alerts for teams or single profile - includes event-based push notifications by email or mobile device
- ONVIF compliant
- SNMPv3, Multi-VLAN, and enterprise ready
- Updates of firmware and agent apply automatically
- Fanless design for silent operation
- Get your no obligation free trial at domotz.com/pricing.php

Specifications:

Standards

- IEEE 802.3i (10BASE-T)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (Twisted-Pair Gigabit Ethernet)

General

- Processor: Allwinner H618, Quad-core ARM Cortex-A53, 1.5 GHz · ARMv8-A (64-bit)
- RAM: 1 GB
- Storage: 8 GB eMMC
- Network connectivity: one Gigabit RJ45 port
- One USB 2.0 Type-A port for future releases
- LED indicator
- Factory reset button
- Certifications: CE, RoHS, REACH, FCC, UKCA

Power

- Power input: USB-C port
- Included external power adapter
 - Input 100 - 240 V AC, 50 - 60 Hz, 0.5 A
 - Output: USB-C plug, 5.0 V DC, 2.0 A
- Power consumption: 10.0 W max.

Physical

- Dimensions (L x W x H): 108 x 72 x 40 mm (4.25 x 2.81 x 1.63 in.)
- Net weight: 126 g (0.28 lbs.)
- Gross weight: 500 g (1.1 lbs.)

Environmental

- Operating temperature: 0 to 40°C (32 to 104°F)
- Operating humidity: 80% RH max., non-condensing

Package Contents

- Domotz Pro Box C-1
- Flat Gigabit Ethernet cable
- Power adapter
- Quick installation guide



