




Cat6 U/UTP Premium Network Patch Cable, 1.5 m (5 ft.), Blue, 10-Pack

10G, 250 MHz, 100% Copper, 26 AWG, RJ45, Stranded, Snag-free, Gold-plated Contacts

SKU: 746557 | EAN-13: 0766623746557 | UPC: 766623746557

Cat6 Ethernet Cable 1.5m Blue 10pcs - 10G, 250 MHz LAN Patch Cord

Establish your high-performance network connections with this Cat6 Network Patch Cable from Intellinet Network Solutions. It supports up to 10 Gbps data transmissions with frequencies up to 250 MHz and all PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE.

Pure copper cable with gold-plated contacts for perfect conductivity

As opposed to other cables that are manufactured with copper-clad aluminum (CCA) or even copper-clad steel (CCS), this cable contains 100% pure bare copper for perfect conductivity, making it ideal for use in PoE applications. Gold plating on the contacts makes them corrosion-resistant in every environment.

Gold-plated contacts for perfect conductivity

Gold plating on the contacts makes them corrosion-resistant in every environment.

Snag-free Boot Design

The snag-free boot design makes all patch cables from Intellinet Network Solutions the perfect choice for high-density environments, like data centers or server rooms. The cable plugs are equipped with strain relief and a molded boot for protection that makes it easy to safely connect and disconnect the latch without breaking it.

Features:

- Cat6 with 10G / 1G and 250 MHz in accordance with ISO/IEC 11801 and EN 50288
- Gold-plated contacts for corrosion-free connections
- Snag-free boots to smoothly and easily pull the cable without damaging the RJ45 connectors
- Ideal for HDBaseT and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- PVC cable jacket with heavy-duty strain relief for flexibility and durability
- Standard 8P8C design, compatible with all network RJ45 connections
- Compatible and color-coded with T568A and T568B
- Fully backward compatible with previous cable categories, including Category 5e and 5
- UL listed
- Convenient multi-pack includes ten cables for multiple devices and locations
- Lifetime warranty

Specifications:

Standards and Certifications

- ISO/IEC 11801
- EN 50288
- UL
- CE
- RoHS
- REACH
- UKCA
- 10BASE-T / 100BASE-TX / 1000BASE-T / 10GBASE-T
- ANSI/TIA-568.2-D

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

General

- Cat6-certified
- Supported transfer speeds: up to 10 Gbps
- Max. operating frequency: 250 MHz
- Supports all PoE standards up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE

Connectors

- Two RJ45 male
- Contacts: gold-plated
- Mating cycles: ≥ 750

Cable

- Conductor gauge: 26 AWG
- Shielding: U/UTP
- Jacket material: PVC, UL-CM rated
- Jacket OD: 4.9 mm (0.19 in.)
- Jacket thickness: 0.55 mm (0.02 in.)
- Wire: 100% pure bare copper (Cu)
- Conductor type: stranded
- Cable type: round
- Minimum bending radius: 15 x OD during operation, 10 x OD after installation
- Conductor resistance: $\leq 16.5 \text{ Ohm}/100 \text{ m}$ @ 20°C
- Dielectric strength: 1500 V DC / 1 min
- Resistance unbalance: $\leq 2\%$
- Capacitance unbalance: $\leq 220 \text{ pF}/100 \text{ m}$

Size and weight


- Length: 1.5 m (5 ft.)
- Net weight (10-pack): 433 g (0.95 lbs.)
- Gross weight (10-pack): 443 g (0.98 lbs.)


Environmental

- Operating temperature: -20 to 60°C (-4 to 140°F)
- Storage temperature: -20 to 75°C (-4 to 167°F)
- Operating humidity (non-condensing): 10 to 90% RH

Package Contents

- Cat6 U/UTP Premium Network Patch Cable, 10 pcs





10
Pack



10
Pack



10
Pack

