



Wireless 300N 3G Router

300 Mbps, 2T2R MIMO, 3G, 4-Port 10/100 Mbps LAN Switch

Part No.: **524681**

EAN-13: 0766623524681 | UPC: 766623524681

The INTELLINET NETWORK SOLUTIONS Wireless 300N 3G Router is the latest in wireless networking. Taking advantage of new technology, a wireless network can now see greatly enhanced network speeds and the convenience of 3G mobile technology.

Shares 3G / 3.5G Internet Connection

The INTELLINET NETWORK SOLUTIONS Wireless 300N 3G Router is a high-speed wireless 3G broadband router that supports both UMTS/HSDPA and EVDO networks. When connecting a 3G / 3.5G USB modem* to the router, all network (wired/wireless) users can share the 3G / 3.5G Internet connection. The Wireless 300N 3G Router can support 3G / 3.5G speed up to 7.2 Mbps.

Multiple Solutions in One Device

The INTELLINET NETWORK SOLUTIONS Wireless 300N 3G Router serves multiple purposes — an access point for your wireless network, a 4-port router for hard-wiring Ethernet devices — and brings it all together so that the devices can access a high-speed Internet connection.

Automatic WAN Fail-Over

The INTELLINET NETWORK SOLUTIONS Wireless 300N 3G Router supports automatic WAN fail-over function. When connecting with DSL/Cable broadband, the Wireless 300N 3G Router will enable the DSL/Cable broadband connection automatically when a 3G / 3.5G Internet connection is not available. You can surf the Internet anywhere and anytime.

* For a complete list of compatible 3G USB modems, visit www.intellinet-network.com.

Features:

- Supports UMTS/HSDPA and EVDO 3G networks
- Up to 300 Mbps network link speed
- Complies with 2.4 GHz IEEE 802.11n standard and is backward compatible with IEEE 802.11g/b standards
- 2T2R MIMO technology for enhanced throughput and coverage

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Supports WMM function to meet the multimedia data bandwidth requirement
- Supports Wi-Fi Protected Setup (WPS)
- Supports WAN connection auto fail-over
- Supports WEP and WPA/WPA2 (TKIP and AES) data encryption
- DHCP server supports static lease management
- Supports virtual server, port forwarding and DMZ (demilitarized zone)
- Supports DDNS (dynamic DNS)
- Supports UPnP (Universal Plug and Play)
- Integrated anti-DOS firewall
- QoS (Quality of Service) bandwidth management
- VPN Passthrough (PPTP/IPSec)
- Integrated USB 2.0 port for UMTS/HSDPA and EVDO 3G modems
- Use INTELLINET NETWORK SOLUTIONS Wireless N adapters for the best compatibility and performance
- Easy installation through Web-based user interface
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.1d (Spanning Tree Protocol)
- IEEE 802.11b (11 Mbps Wireless LAN)
- IEEE 802.11g (54 Mbps Wireless LAN)
- IEEE 802.11n (300 Mbps Wireless LAN)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- LAN ports: 4 RJ45 10/100 Mbps data ports
- LAN ports with Auto MDI/MDI-X
- WAN port: 10/100 Mbps RJ45 connector
- USB 2.0 port: 3G/3.5G USB modem
- Flash: 4 MB
- Memory: 16 MB SDRAM
- Certifications: FCC Class B, CE Mark
- For a complete list of compatible 3G USB modems, visit www.intellinet-network.com

Router

- Supported WAN connection types:
 - 3G / 3.5G
 - Dynamic IP
 - Static IP
 - PPPoE
 - PPTP
 - L2TP

- Telstra BigPond
- Protocols:
 - CSMA/CA
 - CSMA/CD
 - TCP/IP
 - UDP
 - ICMP
 - PPPoE
 - NTP
 - NAT
 - DHCP
 - DNS
- NAT:
 - Virtual server
 - Port forwarding
 - Special applications (port trigger)
- Firewall:
 - Access control based on MAC address
 - URL filter
 - DMZ (demilitarized zone)
- Supports UPnP (Universal Plug and Play)
- Supports DHCP (client/server)
- Supports WPS (WiFi Protected Setup)
- VPN passthrough: PPTP, IPSec protocol

Wireless

- Chipset: Ralink RT3052
- Wireless frequency range: 2.400 – 2.483 GHz
- Modulation technologies:
 - 802.11b: Direct Sequence Spread Spectrum (DSSS): DBPSK, DQPSK, CCK
 - 802.11g: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
 - 802.11n: Orthogonal Frequency Division Multiplexing (OFDM): BPSK, QPSK, 16QAM, 64QAM
- Channels:
 - USA & Canada: 11 channels
 - Europe: 13 channels
 - Japan: 14 channels
- Data rates:
 - IEEE 802.11b (11 Mbps, 5.5 Mbps, 2 Mbps, 1 Mbps)
 - IEEE 802.11g (54 Mbps, 48 Mbps, 36 Mbps, 24 Mbps, 18 Mbps, 12 Mbps, 9 Mbps, 6 Mbps)
 - IEEE 802.11n (MCS0-07: up to 150 Mbps)
 - IEEE 802.11n (MCS0-15: up to 300 Mbps)
- Output power:
 - OFDM: 15 dBm +/- 1 dBm (300 Mbps, 40 mW max.)
 - OFDM: 15 dBm +/- 1 dBm (54 Mbps, 40 mW max.)

- CCK: 17 dBm +/- 1 dBm (11 Mbps, 63 mW max.)
- Receiver sensitivity:
 - 11n (300 Mbps) MCS0-15: 20 MHz: -73 dBm; 40 MHz: -68 dBm
 - 11g (54 Mbps) OFDM: -78 dBm
 - 11b (11 Mbps) CCK: -91 dBm
- Maximum coverage distance: 100 m / 328 ft. (indoors); 300 m / 980 ft. (outdoors)
- Wireless security:
 - WEP encryption (64/128 bit)
 - WPA TKIP
 - WPA2 AES
 - WPA2 mixed
 - WPA RADIUS
 - Client access control through media access control (MAC) filter
- Antennas:
 - 2 fixed dipole antennas with 3 dBi gain each
 - 2T2R MIMO mode (2 transmitters, 2 receivers)

LEDs

- Power
- WLAN Link/Act
- LAN 1-4 Link/Act
- USB

Environmental

- Dimensions: 157 (W) x 127 (L) x 30 (H) mm (6.2 x 5.0 x 1.2 in.)
- Weight: 0.215 kg (7.58 oz.)
- Operating temperature: 10 – 40°C (50 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -20 – 60°C (4 – 149°F)

Power

- External power adapter: 12 V DC, 1.0 A
- Power consumption: 5 Watts max.

Package Contents

- Wireless 300N 3G Router
- User manual
- Power adapter
- Ethernet Cat5 RJ45 cable: 1.0 m (3 ft.)
- USB extension cable: 1.0 m (3 ft.)

