



PTZ Network IP Camera

PROFESSIONAL SERIES

Model
550734

Full Remote Control of the Camera, with Pan, Tilt, and Zoom Capability Right from the Computer.

This PTZ Network IP Camera is equipped with a zoom lens, indoor/outdoor enclosure, pan/tilt motor, and control box, making it an ideal tool for your most critical surveillance operations. One camera becomes very powerful, minimizing the number of cameras required overall to provide coverage for the area under surveillance.

Pan, Tilt, and Zoom Controlled via Web Browser

This **PTZ Network IP Camera** features an 8X zoom lens, 350 degrees horizontal pan coverage, and 90 degrees vertical tilt capability, all controlled from your Web browser!

Indoor/Outdoor Enclosure & Control Box

The **PTZ Network IP Camera** is housed in an enclosure capable of protecting your camera inside or outside, giving you the flexibility to place it where needed, without having to purchase different models for indoor use, and other models for outdoor use.

Multiple Log-In

Because this **PTZ Network IP Camera** supports up to 100 users simultaneously, it can be used in commercial applications that require several people to access the camera at the same time. A perfect example of this would be multiple security guard stations, or multiple sets of parents viewing their children in class or day care.

User Based Frame Rate Control

Unlike SOHO based Network IP Cameras, this Professional Series camera allows you to prioritize users by determining who gets the most bandwidth allocated to them when multiple users are accessing the camera simultaneously.

Web-View Software

View up to four cameras simultaneously using the Multi-Viewer software included with the camera. View the front lobby, parking lot, elevator bay, and roof access all at the same time from one screen.

Software Developer Support

Extensive support is available for software developers who provide customized solutions to their clients. An API allows you to control the parameters of the PTZ Network IP Camera using customer built applications (Visual Basic, ASP, PHP, etc.). The support website includes documentation on Webview OCX and ActiveX, a list of supported video surveillance & recording software vendors, bandwidth requirement charts, access to live cameras for sample viewing, and more.

Motion Detection

The built in sensor can detect motion, and can be configured to send an E-mail with an attached snapshot, upload images to an FTP server, or initiate recording through most third party video surveillance and recording software programs.

Lifetime Warranty

Strict manufacturing standards assure the highest quality in all **INTELLINET NETWORK SOLUTIONS** products. All items carry a full Lifetime Warranty; the strongest quality commitment anyone can make.





Features

8X ZOOM LENS

Provides close up view of area and subjects under surveillance.

350 DEGREE PAN, 90 DEGREE TILT

Provides wide range of coverage, requiring fewer cameras to provide complete surveillance.

BROWSER CONTROLLED CAMERA MOTION

Unlike continuous pan motor based cameras, the PTZ Network IP Camera allows you to control the pan and tilt angle right from your browser, enhancing the level of surveillance and increasing the level of security provided to the business owner and their patrons.

INDOOR/OUTDOOR ENCLOSURE

Standardize on this camera model for all your needs, avoiding the need to purchase multiple models that are limited to either indoor or outdoor use. Protect the camera against vandalism as well as the outdoor elements of the weather.

EMBEDDED OPERATING SYSTEM

Eliminates the need for dedicated personal computers or servers.

BUILT-IN MOTION DETECTION, RECORDING & NOTIFICATION

Sends Automatic Security Alert E-mail, including a Before, During, & After Video History.

MULTIPLE LOG IN

Support up to 100 users simultaneously.

FTP UPLOAD

Transmits live images to any Web Page for Online Promotion.

IMAGE CAPTURE

Saves images on your PC (when using Microsoft Internet Explorer).

ADVANCED VIDEO COMPRESSION

XviD Video compression ensures the best image quality small video file sizes (when saving video with Microsoft Internet Explorer).

QUICK & EASY 3-STEP SETUP

The IP Installer Application lets you quickly find the camera on your network and assign a new IP Address.

SIMULTANEOUS VIEWING

Includes a Multi-Viewer software utility that allows you to monitor up to four cameras at the same time. The advanced video compression produces a high-quality, high-frame rate, VGA, CIF video stream.

INTEGRATED DDNS CLIENT

Utilize the free DYNDNS.ORG service in order to connect to your camera, even if you do not have a static IP Address assigned by your ISP (Internet Service Provider). This feature lets you set up a URL easily, that can be used to access the camera through the internet using any Web browser.

CGI API FOR REMOTE PROGRAMMING

Control the parameters of the PTZ Network IP Camera from within your own application (such as web-based PHP, ASP, or VB applications).

ACTIVEV OXC CONTROLS FOR VISUAL BASIC APPLICATIONS

Quickly develop customized Visual Basic Applications utilizing the Professional Network IP Camera's OXC control.

DIRECT IMAGE ACCESS (HTTP://CAMERA/JPG/IMAGE.JPG)

for better compatibility to 3rd party video surveillance software.

USER BASED FRAME RATE CONTROL

Reserve bandwidth for selected users (i.e. Power Users).

SYNCHRONIZATION WITH NTP SERVERS

The PTZ Network IP Camera allows you to synchronize the time interval with NTP Servers, making it ideal for time critical applications.

6 PORT GPIO CONNECTOR

Supports connection to external sensors and can be used to power external devices.

STANDARD IMAGE FORMAT

The PTZ Network IP Camera delivers complete, high-quality pictures in standard JPEG format, which can be viewed using any standard JAVA enabled Web browser.

Specifications

GENERAL

- Built in Web server
- Pan, tilt, and zoom controlled via Web browser
- Built-in motion detection
- Event-triggered E-mail notification
- 30 frames per second full motion video
- Up to 100 simultaneous users
- Power Over Ethernet Ready
- Password protected user access
- Input to trigger external events
- Configurations for image and security settings
- Firmware upgrade via Internet

NETWORK

- Standard RJ-45 twisted pair cable
- Integrated HTTP Server and FTP client
- JAVA or ActiveX
- Protocols supported: TCP/IP, ARP, FTP, HTTP, PING (Option) POP3, SMTP, SNMP, MIBII, Proxy Agent, BOOTP, DHCP, DNS, Telnet, etc.
- Maximum Throughput: 9 Mbps

SYSTEM REQUIREMENTS

- Windows 98 or higher, Me, 2000, XP, Linux, and Mac
- Internet Explorer 4.0 or higher
- Netscape Navigator 6.0 or higher
- Mozilla, Firefox, Opera, Safari, or Camino

IMAGE COMPRESSION

- Resolution: 640 x 480, 320 x 240, 160 x 120
- 10 levels of JPEG image compression
- XviD Video Compression when recording via Microsoft Internet Explorer
- Compression: High 80:1, Low 3:1

HARDWARE

- Indoor/outdoor housing
- Pan & tilt motor assembly
- Control box
- 32 bit RISC CPU with network enhancement
- 384 kByte video frame buffer
- 2 mByte flash memory
- 8 mByte SDRAM

IMAGE SENSOR AND LENS

- 8 x zoom lens
- 1/3" CMOS lens
- 326,668 pixels, 24-bit color, YUV digital output
- Automatic exposure / gain / white balance control
- 2.5 minimum Lux
- Image control, brightness, contrast, saturation, hue, exposure, sharpness
- 664 x 492 pixel array elements
- Electronic shutter: 1/30 s ~ 1/15734 s
- Backlight compensation
- Replaceable standard CS mount lens
- Focal length 6.0 mm
- Angular field of view 54 degrees
- Object distance 0.1 m to infinity
- Maximum relative aperture f1.8

OPERATING TEMPERATURE

- 0-50°C / 32-122°F

APPROVALS

- EMC: FCC Class A, CE EN55022/1994, EN61000-3-2 & 3: 1995, EN50082-1: 1997

PRODUCT DIMENSIONS

- Camera: 14.73 x 8.64 x 4.06 cm (5.8 x 3.4 x 1.6 in.)
- Weight: 51 lbs. (23.1 kg)

PACKAGE CONTENTS

- Network IP Camera – Professional Series
- Indoor/outdoor enclosure
- Control box with 6 ft. cable
- Pan/tilt motor
- Quick & Easy Setup Guide
- User Manual
- Software CD with User Manual, Drivers, and Utilities

**LIFETIME
WARRANTY**



Remote
Computer



INTERNET



Desktop PC



Router



PTZ
Security Camera

**Model
550734**



INTELLINET
NETWORK SOLUTIONS
BRINGING NETWORKS TO LIFE

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit www.intellinet-network.com.

Copyright © INTELLINET NETWORK SOLUTIONS

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, use and disclosure of the contents herein are prohibited, unless specifically authorized.

INT-550734-DS-020906