



UltraLynk USB 3.0 Gigabit Adapter

Three-Port USB 3.0 Hub with Gigabit Ethernet Port

Part No.: [506892](#)

EAN-13: 0766623506892 | UPC: 766623506892

Made specifically with today's busy Ultrabook owner in mind, the Manhattan UltraLynk is a three-port USB 3.0 hub that also features a high-performance gigabit network adapter. Once connected to an available USB 3.0 port on your Ultrabook or PC, the UltraLynk expands your connection offerings by providing you with three extra SuperSpeed USB ports for peripherals and external drives, as well as an RJ45 Gigabit Ethernet port that lets you connect to a network at up to 1000 Mbps speeds.

Faster Throughput through SuperSpeed USB 3.0

Similar USB hubs with Ethernet adapters cannot even come close to the performance levels of the UltraLynk. This is because they are limited by a USB 2.0 connection that is design to a theoretical maximum of 480 Mbps. The UltraLynk knows no such limitations and delivers true gigabit performance without compromises.

Powerful, Fast SuperSpeed USB Performance in a Multiport Hub

The Manhattan SuperSpeed USB 3.0 to Gigabit Ethernet Adapter comes with three USB ports, easily expanding USB access for Ultrabooks and PCs. Users can connect external storage drives, webcams and more at speeds of 5 Gbps. Plus it's backwards compatible with previous USB standards, plug-and-play ready and hot-swap capable.

Portable Design

The UltraLynk is compact and can be easily used from one computer to another or transferred in your notebook case as you travel. It doesn't take up a lot of space, and doesn't add clutter to your workspace.

Features:

- Upgrade the USB and Ethernet capabilities of your Ultrabook or PC
- Provides 3 SuperSpeed USB 3.0 ports for additional drives and peripherals
- One Gigabit Ethernet (10/100/1000) port for faster downloads, media streaming and gaming
- Hot-swappable (no need to power down)
- Reverse compatible to Hi-Speed USB 2.0 and Fast Ethernet (10/100)
- Works with Ultrabooks and PCs running Windows XP, Vista, Windows 7 or Windows 8 or Windows 10
- Compatible with Mac OS X
- Powered by USB port or optional AC power adapter (not included)
- Three-Year Warranty

Specifications:

Standards

- USB Specification version 3.0
- USB Specification version 2.0
- USB Specification version 1.1
- USB Specification version 1.0
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- USB type-A connector
- RJ45 connector
- (3) downstream ports, USB 3.0 Standard-A
- Connector for 5V DC universal power adapter (optional, not included)
- Certifications: FCC Class B, CE, RoHS

LEDs

- Link
- 10/100/1000 Mbps

Power

- USB bus-powered
- Operating mode: 420 mA
- Suspend mode: 38 mA

Environmental

- Dimensions: 75 (W) x 51.5 (D) x 16.5 (H) mm (2.95 x 2.03 x 0.65 in.)
- Weight: 168 g (5.92 oz.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Storage temperature: -10 – 80°C (14 – 176°F)
- Storage humidity: 5 – 85%, non-condensing

System Requirements

- Desktop or laptop system with USB 1.1, USB 2.0 or USB 3.0 port
- Windows XP/Vista/Windows 7/8/10, Mac OS 10.6 and later

Package Contents

- UltraLynk SuperSpeed USB 3.0 to Gigabit Ethernet Adapter with 3-Port USB Hub
- Setup CD
- Instructions



