

# MASHIKO 900 7328

SKU 1121025

astro



## PRODUCT SPECIFICATION

### GENERAL

|                           |                                                    |                   |                                                        |
|---------------------------|----------------------------------------------------|-------------------|--------------------------------------------------------|
| FINISH:                   | Polished Chrome                                    | GROSS WEIGHT:     | 7.94 (lbs)                                             |
| MAIN MATERIAL:            | Metal - Mild Steel                                 | CLASS:            | cETLus (Class I)                                       |
| DIMENSIONS:               | H:900mm W:80mm D: 80mm<br>H:35.4" W:3.14" D: 3.14" | LISTING LOCATION: | Damp                                                   |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical / Horizontal                 | FITTING METHOD:   | 1/2" StubMount 4" Octagon Box with included Canopy Kit |
| CUT OUT HOLE:             | Not Applicable                                     | ADA COMPLIANT:    | Yes                                                    |
| RECESS DEPTH:             | Not Applicable                                     | IC RATING:        | Not Applicable                                         |
| FIRE RATING:              | Not Applicable                                     | VOLTAGE:          | Mains 120 (V)                                          |
| CABLE LENGTH:             | Not Applicable                                     |                   |                                                        |

### LAMP

|                      |                |                            |                 |
|----------------------|----------------|----------------------------|-----------------|
| LIGHT SOURCE:        | T5 High Output | MACADAM ELIPSE:            | Not Applicable  |
| MAXIMUM WATTAGE:     | 1 x 39W        | UGR:                       | Not Applicable  |
| MAXIMUM LAMP LENGTH: | Not Applicable | BEAM ANGLE:                | 127.3 (Degrees) |
| LAMP INCLUDED?       | No             | TILT ADJUSTMENT ANGLE:     | Not Applicable  |
| DELIVERED LUMENS:    | 1529 (lm)      | ROTATION ADJUSTMENT ANGLE: | Not Applicable  |
| COLOR TEMP:          | To Be Advised  | AVERAGE LIFESPAN:          | 12,000 (Hrs)    |
| CRI:                 | To Be Advised  | L70:                       | Not Applicable  |
| R9:                  | Not Applicable |                            |                 |


### ELECTRICAL

|                        |                |                           |                |
|------------------------|----------------|---------------------------|----------------|
| SWITCHED:              | No             | SUPPLY FREQUENCY:         | 50/60 (Hz)     |
| DIMMABLE:              | No             | DRIVER / BALLAST VOLTAGE: | 120 (V)        |
| DIMMING METHOD:        | Not Applicable | DRIVER AVERAGE LIFESPAN:  | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY:                 | 40.65 (lm/w)   |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER INCLUDED?          | Yes (Integral) |

## ADDITIONAL INFORMATION



This product is not suitable for use with a PIR motion detector.



BOX QUANTITY X6



PRODUCT ELEVATIONS

