



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Polished Chrome	<b>GROSS WEIGHT:</b>	To Be Advised
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>CLASS:</b>	cETLus (Class I)
<b>DIMENSIONS:</b>	H: 315mm W: 125mm D: 315mm H: 12.40" W: 4.92" D: 12.40"	<b>LISTING LOCATION:</b>	Dry
<b>INSTALLATION ORIENTATION:</b>	Wall Mount	<b>FITTING METHOD:</b>	4" Octagon Box
<b>CUT OUT HOLE:</b>	Not Applicable	<b>ADA COMPLIANT:</b>	No
<b>RECESS DEPTH:</b>	Not Applicable	<b>IC RATING:</b>	Not Applicable
<b>FIRE RATING:</b>	Not Applicable	<b>VOLTAGE:</b>	Mains 120 (V)
<b>CABLE LENGTH:</b>	Not Applicable		


### LAMP

<b>LIGHT SOURCE:</b>	E26/Medium	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	43W Max	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	114mm / 4.49"	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	90 (Degrees)
<b>DELIVERED LUMENS:</b>	Lamp Dependent	<b>ROTATION ADJUSTMENT ANGLE:</b>	330 (Degrees)
<b>COLOR TEMP:</b>	Lamp Dependent	<b>AVERAGE LIFESPAN:</b>	Lamp Dependent
<b>CRI:</b>	Lamp Dependent	<b>L70:</b>	Not Applicable
<b>R9:</b>	Lamp Dependent		

### ELECTRICAL

<b>SWITCHED:</b>	Yes	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Lamp Dependent	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	Lamp Dependent
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER / BALLAST INCLUDED?</b>	Not Applicable

## ADDITIONAL INFORMATION



BOX QUANTITY  
To Be Advised

# PRODUCT ELEVATIONS

---

