

# BLOC 7430

SKU 1146010

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Polished Silver	<b>GROSS WEIGHT:</b>	To Be Advised
<b>MAIN MATERIAL:</b>	Metal - Zinc	<b>CLASS:</b>	ETL (Class 2)
<b>DIMENSIONS:</b>	H:100mm W:35mm D: 50mm H:3.93" W:1.37" D:1.96"	<b>LISTING LOCATION:</b>	Damp
<b>INSTALLATION ORIENTATION:</b>	Wall Mount - Vertical	<b>FITTING METHOD:</b>	1/2" Stub Mount
<b>CUT OUT HOLE:</b>	Not Applicable	<b>ADA COMPLIANT:</b>	Yes
<b>RECESS DEPTH:</b>	Not Applicable	<b>IC RATING:</b>	Non IC Rated
<b>FIRE RATING:</b>	Not Applicable	<b>VOLTAGE:</b>	Constant Current 350mA
<b>CABLE LENGTH:</b>	Not Applicable		


### LAMP

<b>LIGHT SOURCE:</b>	High Power LED	<b>MACADAM ELIPSE:</b>	3-Step
<b>MAXIMUM WATTAGE:</b>	2 x 1W	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	Yes (Integral)	<b>TILT ADJUSTMENT ANGLE:</b>	Not Applicable
<b>DELIVERED LUMENS:</b>	58 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	Not Applicable
<b>COLOR TEMP:</b>	3000 (K)	<b>AVERAGE LIFESPAN:</b>	60,000 (Hrs)
<b>CRI:</b>	85	<b>L70:</b>	To Be Advised
<b>R9:</b>	To Be Advised		

### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	No	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Not Applicable	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	17.58 (lm/w)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER INCLUDED?</b>	No

## ADDITIONAL INFORMATION



BOX QUANTITY  
To Be Advised

PRODUCT ELEVATIONS

