

APRILIA TWIN ADJUSTABLE 5688

SKU 1256001

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Matt White	GROSS WEIGHT:	1.39 (lbs)
MAIN MATERIAL:	Metal - Aluminium	CLASS:	cETLus (Class 2)
DIMENSIONS:	H: 180mm W: 95mm D: 69mm H: 7.09" W: 3.74" D: 2.72"	LISTING LOCATION:	Dry
INSTALLATION ORIENTATION:	Ceiling Mount	FITTING METHOD:	Recessed in Drywall Ceiling
CUT OUT HOLE:	H: 165mm/6.5" W: 85mm/3.35"	ADA COMPLIANT:	Not Applicable
RECESS DEPTH:	150mm/5.9"	IC RATING:	Non IC Rated
FIRE RATING:	Not Applicable	VOLTAGE:	Constant Current 350 (mA)
CABLE LENGTH:	Not Applicable		


LAMP

LIGHT SOURCE:	COB LED	MACADAM ELIPSE:	3-Step
MAXIMUM WATTAGE:	2 x 7W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	36.1 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	35 (Degrees)
DELIVERED LUMENS:	976.3 (lm)	ROTATION ADJUSTMENT ANGLE:	360 (Degrees)
COLOR TEMP:	3000 (K)	AVERAGE LIFESPAN:	50,000 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	18		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	76 (lm/w)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	No

ADDITIONAL INFORMATION



BOX QUANTITY X 20

PRODUCT ELEVATIONS

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

