

# BORG0 55

astro

## GENERAL

CLASS:	cETLus (Class 2)
LISTING LOCATION:	Dry
VOLTAGE:	Constant Current 700mA
INSTALLATION ORIENTATION:	Wall mount - vertical
FITTING METHOD:	Recessed in Drywall Wall
MAIN MATERIAL:	Metal - Mild steel
DIMENSIONS:	H: 170mm W: 55mm D: 44mm H: 6.69" W: 2.17" D: 1.73"
CUT OUT HOLE:	L: 6.30" W: 1.89"
RECESS DEPTH:	42mm/1.65"
FIRE RATING:	Not applicable
CABLE LENGTH:	Not applicable
GROSS WEIGHT:	1.19lbs
ADA COMPLIANT:	Yes
IC RATING:	Not applicable

## LAMP

LIGHT SOURCE:	HIGH POWER LED
MAXIMUM WATTAGE:	2W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH:	Not applicable
LUMINOUS FLUX:	38.8 lm
COLOUR TEMP:	3000K
CRI:	80
R9:	To Be Advised
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE:	Not applicable
ROTATION ADJUSTABLE ANGLE:	Not applicable
AVERAGE LIFESPAN:	60,000hrs
L70:	>60,000hrs
BEAM ANGLE:	Not applicable

## ELECTRICAL

SWITCHED:	No
DIMMABLE:	Yes
DIMMING METHOD:	Control Gear Dependent
DRIVER INCLUDED:	Not applicable
DRIVER OUTPUT CURRENT:	Not applicable
DRIVER OUTPUT VOLTAGE:	Not applicable
SUPPLY FREQUENCY:	Not applicable
DRIVER/BALLAST VOLTAGE:	Not applicable
DRIVER AVERAGE LIFESPAN:	Not applicable
EFFICACY:	9.95lm/W

## ADDITIONAL INFORMATION

SHADE INCLUDED	Not applicable
SHADE MATERIAL	Not applicable



CODE: 7089  
SKU: 1212010  
FINISH: POLISHED STAINLESS STEEL TRIM

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

# PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

