

RIO 325 LED

astro

GENERAL

LOCATION:	Interior
CLASS:	cETLus (Class 1)
LOCATION RATING:	Dry
VOLTAGE:	Mains 120V
INSTALLATION ORIENTATION:	Wall Mount - Horizontal
FITTING METHOD:	1/2in Stub Mount 3x2in Switch Box 4in Octagon Box with included Canopy Kit
MAIN MATERIAL:	Plaster
DIMENSIONS:	H: 180mm W: 325mm D: 60mm H: 7.09" W: 12.80" D: 2.36"
CUT OUT HOLE:	Not Applicable
RECESS DEPTH:	Not Applicable
FIRE RATING:	Not Applicable
CABLE LENGTH:	Not Applicable
GROSS WEIGHT:	6.20lbs
ADA COMPLIANT:	Yes
IC RATING:	Not Applicable

LAMP

LIGHT SOURCE:	MID-POWER LED
MAXIMUM WATTAGE:	14W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH:	Not Applicable
LUMINOUS FLUX:	1410 lm
COLOUR TEMP:	3000K
CRI:	80
R9:	5.0
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE:	Not Applicable
ROTATION ADJUSTABLE ANGLE:	Not Applicable
AVERAGE LIFESPAN:	60,000hrs
L70:	To Be Advised
BEAM ANGLE:	104°

ELECTRICAL

SWITCHED:	No
DIMMABLE:	No
DIMMING METHOD:	Not Applicable
DRIVER INCLUDED:	Yes (Integral)
DRIVER OUTPUT CURRENT:	700mA
DRIVER OUTPUT VOLTAGE:	Not Applicable
SUPPLY FREQUENCY:	50/60Hz
DRIVER/BALLAST VOLTAGE:	100-277V
DRIVER AVERAGE LIFESPAN:	50,000hrs
EFFICACY:	100.7lm/W

ADDITIONAL INFORMATION

SHADE INCLUDED	Not Applicable
SHADE MATERIAL	Not Applicable



CODE: 1325015 (8480)
FINISH: PLASTER

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

