

# AVLON 900 LED

astro

## GENERAL

|                           |                                         |
|---------------------------|-----------------------------------------|
| LOCATION:                 | Bathroom                                |
| CLASS:                    | cETLus (Class I)                        |
| LOCATION RATING:          | Damp                                    |
| DRIVER REQUIRED:          | Mains 120V                              |
| INSTALLATION ORIENTATION: | Wall Mount - Vertical & Horizontal      |
| FITTING METHOD:           | 4" Octagon Box with included Canopy Kit |
| MAIN MATERIAL:            | Glass - Float                           |
| DIMENSIONS (mm):          | H: 600 W: 900 D: 17-36                  |
| DIMENSIONS (inch):        | H: 23.6 W: 35.43 D: 0.67-1.42           |
| CUT OUT HOLE (mm/inch):   | -                                       |
| RECESS DEPTH (mm/inch):   | -                                       |
| FIRE RATING:              | -                                       |
| CABLE LENGTH (mm/inch):   | -                                       |
| GROSS WEIGHT (lb):        | 26.4                                    |
| ADA COMPLIANT:            | Yes                                     |
| IC RATING:                | -                                       |

## LAMP

|                                |                |
|--------------------------------|----------------|
| LIGHT SOURCE:                  | Mid-Power LED  |
| WATTAGE:                       | 20.9W          |
| LAMP INCLUDED:                 | Yes (Integral) |
| MAXIMUM LAMP LENGTH (mm/inch): | -              |
| LUMINOUS FLUX (lm):            | 573            |
| COLOUR TEMP (K):               | 3000           |
| CRI (Ra):                      | 80             |
| MACADAM ELLIPSE:               | 3-Step         |
| TILT ADJUSTABLE ANGLE (°):     | -              |
| ROTATION ADJUSTABLE ANGLE (°): | -              |
| LIFETIME (hrs):                | 54000          |
| BEAM ANGLE (°):                | -              |

## ELECTRICAL

|                             |         |
|-----------------------------|---------|
| SWITCHED:                   | No      |
| DIMMABLE:                   | Yes     |
| DIMMING METHOD:             | 0-10V   |
| SUPPLY FREQUENCY (Hz):      | 50/60   |
| DRIVER/BALLAST VOLTAGE (V): | 100-277 |
| DRIVER LIFETIME (hrs):      | 63500   |
| EFFICACY (lm/W):            | 27      |

## ADDITIONAL INFORMATION:

|                          |         |
|--------------------------|---------|
| SHADE INCLUDED:          | -       |
| SHADE/DIFFUSER MATERIAL: | Metal   |
| SHADE/DIFFUSER FINISH    | Natural |
| F MARK:                  | -       |



CODE: 1359009  
FINISH: MIRROR

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

# PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

