

## SPECIFICATION

TYPE:	Constant Current
DRIVER CURRENT (mA):	350
DRIVER VOLTAGE (V):	N/A
DIMMABLE:	Leading/Trailing Edge
ELECTRICAL CLASS:	Class 2
SUPPLY VOLTAGE (V):	108-132V AC
SUPPLY FREQUENCY (Hz):	50/60
POWER FACTOR:	0.9
MIN. OUTPUT VOLTAGE (V DC):	17.0
MAX. OUTPUT VOLTAGE (V DC):	34.0
MIN. OUTPUT POWER (W):	5.95
MAX. OUTPUT POWER(W):	12.0
INRUSH CURRENT(A):	<20A Max @ 120VAC, cold start 25°C
IP RATING:	IP20/Damp
WORKING TEMPERATURE (°C):	-40 - +90
CONNECTION TYPE:	Flying Leads
LENGTH (mm):	81.3
WIDTH (mm):	33.0
HEIGHT (mm):	20.3
MIN. CIRCULAR APERTURE (mm/inch):	48/1-7/8
MAX. LED DISTANCE (m):	To Be Advised
MANUFACTURER:	Hatch
MODEL NUMBER:	LC12-0350P-120-B



CODE: 6008054

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.