LED DRIVER CC 350MA 15W DIMMING



SPECIFICATION

TYPE: Constant Current

DRIVER CURRENT (mA): 350

DRIVER VOLTAGE (V):

DIMMABLE: Leading/Trailing Edge & 0-10V

ELECTRICAL CLASS: Class 2

SUPPLY VOLTAGE (V): 108-305 AC

SUPPLY FREQUENCY (Hz): 47/63

POWER FACTOR: 0.9

MIN. OUTPUT VOLTAGE (V DC): 24.0

MAX. OUTPUT VOLTAGE (V DC): 42.0

MIN. OUTPUT POWER (W): 8.4

MAX. OUTPUT POWER(W): 14.7

INRUSH CURRENT(A): 6A Half Value Time 200µs @120V

IP RATING: Damp

WORKING TEMPERATURE (°C): -30 - +70

CONNECTION TYPE: Trailing Wires

LENGTH (mm): 84.0

WIDTH (mm): 40.0

HEIGHT (mm): 25.0

MIN. CIRCULAR APERTURE (mm/inch): 48/1-7/8

MAX. LED DISTANCE (m): To Be Advised

MANUFACTURER: Efore

MODEL NUMBER: RCL015-0350A



CODE: 6008061

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.