# ENNA SURFACE ROUND LED

#### GENERAL

LOCATION: Interior

CLASS: cETLus (Class 1)

LOCATION RATING: Dry

DRIVER REQUIRED: Mains 120V INSTALLATION ORIENTATION: Wall Mount

FITTING METHOD: ½" Stub Mount or 4" Octagon Box

Metal - Zinc MAIN MATERIAL: DIMENSIONS (mm): D: 141 Ø: 110 DIMENSIONS (inch): D: 5.5 Ø: 4.33

CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (Ib): 1.54 ADA COMPLIANT: No IC RATING:

## LAMP

LIGHT SOURCE: High Powered LED

WATTAGE: 4.1W

LAMP INCLUDED: Yes (Integral)

MAXIMUM LAMP LENGTH (mm/inch): LUMINOUS FLUX (Im): 149 COLOUR TEMP (K): 2700 CRI (Ra): 80 MACADAM ELLIPSE: 3-Step TILT ADJUSTABLE ANGLE (°): 90 ROTATION ADJUSTABLE ANGLE (°): 330 LIFETIME (hrs): 60000 BEAM ANGLE (°): 17

# FI FCTRICAL

SWITCHED: Yes DIMMABLE: No DIMMING METHOD:

SUPPLY FREQUENCY (Hz): 50-60 DRIVER/BALLAST VOLTAGE (V): 100-277 DRIVER LIFETIME (hrs): 30000 EFFICACY (Im/W): 36

### ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE/DIFFUSER MATERIAL: SHADE/DIFFUSER FINISH

F MARK: Suitable for mounting

on flammable materials



CODE: 1058123 (8634) FINISH: MATT WHITE



CODE: 1058124 (8635) FINISH: MATT BLACK



CODE: 1058125 (8636) FINISH: MATT NICKEL



CODE: 1058126 (8637) FINISH: BRONZE



CODE: 1058127 (8638) FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.







