

DUNBAR 160

astro

GENERAL

LOCATION:	Exterior
CLASS:	cETLus (Class 1)
LOCATION RATING:	Wet
DRIVER REQUIRED:	No
INSTALLATION ORIENTATION:	Wall Mount - Vertical
FITTING METHOD:	4" Octagon Box
MAIN MATERIAL:	Metal - Aluminium
DIMENSIONS (mm):	H:160 W:110 D:106
DIMENSIONS (inch):	H: 6.30 W: 4.33 D: 4.17
CUT OUT HOLE (mm/inch):	-
RECESS DEPTH (mm/inch):	-
FIRE RATING:	-
CABLE LENGTH (mm/inch):	-
GROSS WEIGHT (lb):	1.98
ADA COMPLIANT:	Yes - if installed in compliance with ADA 307.2
IC RATING:	-

LAMP

LIGHT SOURCE:	High Powered LED
WATTAGE:	5.8W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH (mm/inch):	-
COLOUR TEMP (K):	3000
CRI (Ra):	90
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE (°):	-
ROTATION ADJUSTABLE ANGLE (°):	-
LIFETIME (hrs):	60000
BEAM ANGLE (°):	-

ELECTRICAL

SWITCHED:	No
DIMMABLE:	No
DIMMING METHOD:	-
SUPPLY FREQUENCY (Hz):	50/60
DRIVER/BALLAST VOLTAGE (V):	100-277
DRIVER LIFETIME (hrs):	30000

ADDITIONAL INFORMATION

SHADE INCLUDED:	-
SHADE MATERIAL:	-
F MARK:	Suitable for mounting on flammable materials



CODE: 1384013
FINISH: TEXTURED WHITE
LUMENS: 240
EFFICACY 42



CODE: 1384014
FINISH: TEXTURED BLACK
LUMENS: 110
EFFICACY 19



CODE: 1384015
FINISH: TEXTURED GREY
LUMENS: 135
EFFICACY 22

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

