

JOEL TABLE

astro

GENERAL

| | |
|---------------------------|---|
| LOCATION: | Interior |
| CLASS: | cETLus (Class 1) |
| LOCATION RATING: | Dry |
| DRIVER REQUIRED: | Mains 120V |
| INSTALLATION ORIENTATION: | - |
| FITTING METHOD: | - |
| MAIN MATERIAL: | Metal - Aluminium |
| DIMENSIONS (mm): | H: 550 D: 470 |
| DIMENSIONS (inch): | H: 21.65 D: 18.5 |
| CUT OUT HOLE (mm/inch): | - |
| RECESS DEPTH (mm/inch): | - |
| FIRE RATING: | - |
| CABLE LENGTH (mm/inch): | 2250 / 88.58 |
| GROSS WEIGHT (lb): | 8.58 |
| ADA COMPLIANT: | Yes - if installed in compliance with ADA 308, 309.3, 309.4 |
| IC RATING: | - |

LAMP

| | |
|--------------------------------|----------------|
| LIGHT SOURCE: | E26/Medium |
| WATTAGE: | 43W |
| LAMP INCLUDED: | No |
| MAXIMUM LAMP LENGTH (mm/inch): | 114 |
| LUMINOUS FLUX (lm): | Lamp Dependent |
| COLOUR TEMP (K): | Lamp Dependent |
| CRI (Ra): | Lamp Dependent |
| MACADAM ELLIPSE: | - |
| TILT ADJUSTABLE ANGLE (°): | 90 |
| ROTATION ADJUSTABLE ANGLE (°): | 330 |
| LIFETIME (hrs): | Lamp Dependent |
| BEAM ANGLE (°): | - |

ELECTRICAL

| | |
|-----------------------------|----------------|
| SWITCHED: | Yes |
| DIMMABLE: | - |
| DIMMING METHOD: | - |
| SUPPLY FREQUENCY (Hz): | - |
| DRIVER/BALLAST VOLTAGE (V): | - |
| DRIVER LIFETIME (hrs): | - |
| EFFICACY (lm/W): | Lamp Dependent |

ADDITIONAL INFORMATION

| | |
|-----------------|---|
| SHADE INCLUDED: | - |
| SHADE MATERIAL: | - |
| F MARK: | - |



CODE: 1223062
FINISH: POLISHED CHROME



CODE: 1223063
FINISH: MATT BLACK



CODE: 1223064
FINISH: CREAM

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

