

MICRO RECESS UNSWITCHED

astro

GENERAL

LOCATION:	Interior
CLASS:	cETLus (Class 2)
LOCATION RATING:	Dry
DRIVER REQUIRED:	Constant Current 700mA
INSTALLATION ORIENTATION:	Wall Mount
FITTING METHOD:	Recessed in Solid Wall or Drywall
MAIN MATERIAL:	Metal - Aluminium
DIMENSIONS (mm):	H: 84 D: 61 Ø: 61
DIMENSIONS (inch):	H: 3.31 D: 2.4 Ø: 2.4
CUT OUT HOLE (mm/inch):	Ø: 17 / 11/16"
RECESS DEPTH (mm/inch):	21 / 0.83
FIRE RATING:	-
CABLE LENGTH (mm/inch):	1000-1050/39.37-41.34
GROSS WEIGHT (lb):	0.54mm
ADA COMPLIANT:	Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4
IC RATING:	Non IC Rated

LAMP

LIGHT SOURCE:	High Power LED
WATTAGE:	2W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH (mm/inch):	-
LUMINOUS FLUX (lm):	164
COLOUR TEMP (K):	2700
CRI (Ra):	80
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE (°):	90
ROTATION ADJUSTABLE ANGLE (°):	330
LIFETIME (hrs):	60000
BEAM ANGLE (°):	21

ELECTRICAL

SWITCHED:	No
DIMMABLE:	Yes
DIMMING METHOD:	Control Gear Dependant
SUPPLY FREQUENCY (Hz):	-
DRIVER/BALLAST VOLTAGE (V):	-
DRIVER LIFETIME (hrs):	-
EFFICACY (lm/W):	51

ADDITIONAL INFORMATION:

SHADE INCLUDED:	-
SHADE/DIFFUSER MATERIAL:	-
SHADE/DIFFUSER FINISH:	-
F MARK:	Suitable for mounting on flammable materials



CODE: 1407011
FINISH: MATT WHITE



CODE: 1407012
FINISH: MATT BLACK



CODE: 1407013
FINISH: MATT NICKEL



CODE: 1407014
FINISH: BRONZE



CODE: 1407015
FINISH: MATT GOLD

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

