

VOID ROUND 80

astro

GENERAL

LOCATION:	Bathroom
CLASS:	cETLus (Class 2)
LOCATION RATING:	Damp
DRIVER REQUIRED:	Constant Current 250mA
INSTALLATION ORIENTATION:	Install in to New Ceiling
FITTING METHOD:	Recessed in Drywall Ceiling
MAIN MATERIAL:	Metal - Aluminium
DIMENSIONS (mm):	H: 177 W: 80 D: 80 Ø: 146
DIMENSIONS (inch):	H: 6.97 W: 3.15 D: 3.15 Ø: 5.75
CUT OUT HOLE (mm/inch):	Ø: 95/3-¾
RECESS DEPTH (mm/inch):	177/6.97
FIRE RATING:	-
CABLE LENGTH (mm/inch):	1000/39.37
GROSS WEIGHT (lb):	2.26
ADA COMPLIANT:	Yes - if installed in compliance with ADA 307.4
IC RATING:	Non IC Rated

LAMP

LIGHT SOURCE:	COB LED
WATTAGE:	9.1W
LAMP INCLUDED:	Yes (Integral)
MAXIMUM LAMP LENGTH (mm/inch):	-
LUMINOUS FLUX (lm):	690
COLOUR TEMP (K):	2700
CRI (Ra):	93
MACADAM ELLIPSE:	3-Step
TILT ADJUSTABLE ANGLE (°):	-
ROTATION ADJUSTABLE ANGLE (°):	-
LIFETIME (hrs):	To Be Advised
BEAM ANGLE (°):	13.65

ELECTRICAL

SWITCHED:	No
DIMMABLE:	Yes
DIMMING METHOD:	Control Gear Dependent
SUPPLY FREQUENCY (Hz):	-
DRIVER/BALLAST VOLTAGE (V):	-
DRIVER LIFETIME (hrs):	-
EFFICACY (lm/W):	77

ADDITIONAL INFORMATION

SHADE INCLUDED:	-
SHADE MATERIAL:	-
F MARK:	Suitable for mounting on flammable materials



CODE: 1392028
FINISH: MATT WHITE

TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

