



SPECIFICATIONS

Comfort Flow™ HD/Scrape™ HD Modular Tile

Product Number 4430 (Comfort Flow with holes)

Product Number 4431 (Comfort Scrape without holes)

Product Number 4432 (Comfort Flow with holes, with grit)

Product Number 4433 (Comfort Scrape without holes, with grit)

Overall Size: Corner Tile- 19.125" x 19.125" and 37.375" x 37.375"
Side Tile- 18" x 19.125" and 36" x 37.375"
Middle Tile- 18" x 18" and 36" x 36"

Rubber Type: Nitrile Rubber High Density Closed Cell Foam

Thickness: 3/4"

Color: Black

Durometer: 50 to 55

Testing

- Passes Flammability Standard DOC-FF-1-70
- ASTM C1028-96 Static Coefficient of Friction: Dry - .87 Wet - .88
- Static Dissipative
 - Surface to Ground 50% Relative Humidity 1.5×10^6 OHMS
 - Surface to Ground 12% Relative Humidity 1.9×10^6 OHMS
 - Surface to Surface 50% Relative Humidity 2.8×10^5 OHMS
 - Surface to Surface 12% Relative Humidity 2.9×10^5 OHMS
- Anti-microbial treated for lifetime protection against odors and degradation
- Grease and Oil Proof
- Welding Safe