



SPECIFICATIONS

Hog Heaven™ Modular Tile II

Product Number: 522- 18" Tiles

Product Number: 523- 36" Tiles

Product Number: 524- 18" Tiles with Grit

Product Number: 525- 36" Tiles with Grit

Product Size: Corner Tile- 21.875" x 21.875"

Middle Tile- 18" x 18"

Side Tile- 18" x 21.875"

Corner Tile- 39.875" x 39.875"

Middle Tile- 36" x 36"

Side Tile- 36" x 39.875"

Type: 100% Nitrile Rubber (20% Recycled Content)

Thickness: 3/4"

Durometer: 40-45

Tensil: 1100 PSI

Cushion

Type: Nitrile Closed Cell Foam

Density: 5.5 to 7.5 lbx/ft³

Water Absorption: ASTM D 1667- .01 lb/sq ft maximum

Temperature Use: ASTM D 1056- Cold Crack: -20 degrees F
High: 200 Degrees intermittent exposure

Testing

- Passes Flammability Standard DOC-FF-1-70
- Electrically Conductive
 - Surface to Ground 50% Relative Humidity 1.7 x 10⁴ OHMS
 - Surface to Ground 12% Relative Humidity 2.9 x 10⁴ OHMS
 - Surface to Surface 50% Relative Humidity 2.6 x 10⁴ OHMS
 - Surface to Surface 12% Relative Humidity 4.9 x 10⁴ OHMS
- ASTM C1028-96 Static Coefficient of Friction: Dry - .92 Wet = .86
- Welding Safe