

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

## 1 Identification

- **Product identifier**
- **Trade name:** 2-Butanone
- **Article number:** 127770
- **CAS Number:**  
78-93-3
- **EC number:**  
201-159-0
- **Index number:**  
606-002-00-3
- **Application of the substance / the mixture** Laboratory chemicals for research and development
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
BeanTown Chemical  
9 Sagamore Park Road  
Hudson, NH 03051  
USA
- Phone: (603) 402-2234  
Fax: (603) 402-9713  
Email: [technical@beantownchem.com](mailto:technical@beantownchem.com)  
[www.beantownchem.com](http://www.beantownchem.com)
- **Information department:** Technical Support Department
- **Emergency telephone number:**  
During normal operating hours, please call (603) 402-2234  
After hours, please call Chemtrec at (800) 424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Butanone

(Contd. of page 1)

- **Hazard-determining components of labeling:**

- 2-Butanone

- **Hazard statements**

- Highly flammable liquid and vapor.

- Causes serious eye irritation.

- May cause drowsiness or dizziness.

- **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

- Use explosion-proof electrical/ventilating/lighting/equipment.

- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

- Continue rinsing.

- Store locked up.

- Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Substances**

- **CAS No. Description**

- 78-93-3 2-Butanone

- **Identification number(s)**

- **EC number:** 201-159-0

- **Index number:** 606-002-00-3

## 4 First-aid measures

- **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately rinse with water.

- **After eye contact:**

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

- No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Butanone

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

200 ppm

· **PAC-2:**

2700\* ppm

· **PAC-3:**

4000\* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:**  
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

**Trade name: 2-Butanone**

(Contd. of page 3)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**78-93-3 2-Butanone**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 590 mg/m <sup>3</sup> , 200 ppm                                                      |
| REL | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm |
| TLV | Short-term value: 885 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 590 mg/m <sup>3</sup> , 200 ppm |
| BEI |                                                                                                       |

· **Ingredients with biological limit values:**

**78-93-3 2-Butanone**

|     |                                                                 |
|-----|-----------------------------------------------------------------|
| BEI | 2 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MEK |
|-----|-----------------------------------------------------------------|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|               |           |
|---------------|-----------|
| <b>Form:</b>  | Liquid    |
| <b>Color:</b> | Colorless |
| <b>Odor:</b>  | Pleasant  |

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Butanone

(Contd. of page 4)

|                                                                                                                                 |                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| · <b>Odor threshold:</b>                                                                                                        | Not determined.                                                                                    |
| · <b>pH-value:</b>                                                                                                              | Not determined.                                                                                    |
| · <b>Change in condition</b><br><b>Melting point/Melting range:</b><br><b>Boiling point/Boiling range:</b>                      | -87 °C (-124.6 °F)<br>80 °C (176 °F)                                                               |
| · <b>Flash point:</b>                                                                                                           | -9 °C (15.8 °F)                                                                                    |
| · <b>Flammability (solid, gaseous):</b>                                                                                         | Not applicable.                                                                                    |
| · <b>Ignition temperature:</b>                                                                                                  | 514 °C (957.2 °F)                                                                                  |
| · <b>Decomposition temperature:</b>                                                                                             | Not determined.                                                                                    |
| · <b>Auto igniting:</b>                                                                                                         | Not determined.                                                                                    |
| · <b>Danger of explosion:</b>                                                                                                   | Product is not explosive. However, formation of explosive air/vapor mixtures are possible.         |
| · <b>Explosion limits:</b><br><b>Lower:</b><br><b>Upper:</b>                                                                    | 1.8 Vol %<br>11.5 Vol %                                                                            |
| · <b>Vapor pressure at 20 °C (68 °F):</b>                                                                                       | 105 hPa (78.8 mm Hg)                                                                               |
| · <b>Density at 20 °C (68 °F):</b><br>· <b>Relative density</b><br>· <b>Vapor density</b><br>· <b>Evaporation rate</b>          | 0.805 g/cm <sup>3</sup> (6.71773 lbs/gal)<br>Not determined.<br>Not determined.<br>Not determined. |
| · <b>Solubility in / Miscibility with</b><br><b>Water at 20 °C (68 °F):</b>                                                     | 290 g/l                                                                                            |
| · <b>Partition coefficient (n-octanol/water):</b>                                                                               | Not determined.                                                                                    |
| · <b>Viscosity:</b><br><b>Dynamic at 20 °C (68 °F):</b><br><b>Kinematic:</b><br><b>Organic solvents:</b><br><b>VOC content:</b> | 0.4 mPas<br>Not determined.<br>100.0 %<br>100.00 %<br>805.0 g/l / 6.72 lb/gal                      |
| <b>Solids content:</b>                                                                                                          | 0.0 %                                                                                              |
| · <b>Other information</b>                                                                                                      | No further relevant information available.                                                         |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
  Incompatible products  
  Heat, flames and sparks
- **Incompatible materials:**  
  Strong oxidizing agents  
  Strong acids

(Contd. on page 6)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

**Trade name: 2-Butanone**

(Contd. of page 5)

Strong bases  
 Strong reducing agents  
 Ammonia  
 Copper  
 Amines

· **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**78-93-3 2-Butanone**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 3,300 mg/kg (rat)    |
| Dermal | LD50 | 5,000 mg/kg (rabbit) |

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Substance is not listed.

· **NTP (National Toxicology Program)**

Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Butanone

(Contd. of page 6)

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

|                                                                                   |                                                                                                                 |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| · <b>UN-Number</b>                                                                | UN1193                                                                                                          |
| · <b>DOT, IMDG, IATA</b>                                                          |                                                                                                                 |
| · <b>UN proper shipping name</b>                                                  | Ethyl methyl ketone                                                                                             |
| · <b>DOT</b>                                                                      | ETHYL METHYL KETONE (METHYL ETHYL KETONE)                                                                       |
| · <b>IMDG, IATA</b>                                                               |                                                                                                                 |
| · <b>Transport hazard class(es)</b>                                               |                                                                                                                 |
| · <b>DOT, IMDG, IATA</b>                                                          |                                                                                                                 |
| · <b>Class</b>                                                                    | 3 Flammable liquids                                                                                             |
| · <b>Label</b>                                                                    | 3                                                                                                               |
| · <b>Packing group</b>                                                            |                                                                                                                 |
| · <b>DOT, IMDG, IATA</b>                                                          | II                                                                                                              |
| · <b>Environmental hazards:</b>                                                   |                                                                                                                 |
| · <b>Marine pollutant:</b>                                                        | No                                                                                                              |
| · <b>Special precautions for user</b>                                             | Warning: Flammable liquids                                                                                      |
| · <b>Hazard identification number (Kemler code):</b>                              | 33                                                                                                              |
| · <b>EMS Number:</b>                                                              | F-E,S-D                                                                                                         |
| · <b>Stowage Category</b>                                                         | B                                                                                                               |
| · <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not applicable.                                                                                                 |
| · <b>Transport/Additional information:</b>                                        |                                                                                                                 |
| · <b>DOT</b>                                                                      |                                                                                                                 |
| · <b>Quantity limitations</b>                                                     | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L                                                 |
| · <b>Hazardous substance:</b>                                                     | 5000 lbs, 2270 kg                                                                                               |
| · <b>IMDG</b>                                                                     |                                                                                                                 |
| · <b>Limited quantities (LQ)</b>                                                  | 1L                                                                                                              |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · <b>UN "Model Regulation":</b>                                                   | UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE), 3, II                                                        |

US

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Butanone

(Contd. of page 7)

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

Substance is not listed.

· **Section 313 (Specific toxic chemical listings):**

Substance is not listed.

· **TSCA (Toxic Substances Control Act):**

ACTIVE

· **Hazardous Air Pollutants**

Substance is not listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

I

· **TLV (Threshold Limit Value)**

Substance is not listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **RTECS**

Substance is not listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **NFPA ratings (scale 0-4)**

Health = 2

Fire = 3

Reactivity = 1

· **HMIS ratings (scale 0-4)**

Health = 2

Fire = 3

Reactivity = 1

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

**Trade name: 2-Butanone**

(Contd. of page 8)

· **Department issuing SDS:** Technical Support Department

· **Contact:** Technical Support Department

· **Date of preparation / last revision** 07/09/2024 / -

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

US