

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

1 Identification

- **Product identifier**
- **Trade name:** 2-Ethoxyethanol
- **Article number:** 133295
- **CAS Number:**
110-80-5
- **EC number:**
203-804-1
- **Index number:**
603-012-00-X
- **Application of the substance / the mixture** Laboratory chemicals for research and development
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
BeanTown Chemical
9 Sagamore Park Road
Hudson, NH 03051
USA

Phone: (603) 402-2234
Fax: (603) 402-9713
Email: technical@beantownchem.com
www.beantownchem.com
- **Information department:** Technical Support Department
- **Emergency telephone number:**
During normal operating hours, please call (603) 402-2234
After hours, please call Chemtrec at (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 1A H360 May damage fertility or the unborn child.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 1)

· Hazard pictograms

· Signal word *Danger*

· Hazard-determining components of labeling:

2-ethoxyethanol

· Hazard statements

Flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

May damage fertility or the unborn child.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description

110-80-5 2-ethoxyethanol

· Identification number(s)

· EC number: 203-804-1

· Index number: 603-012-00-X

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: Immediately call a doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

15 ppm

- **PAC-2:**

1,000 ppm

- **PAC-3:**

6000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:**

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute

· **Control parameters**· **Components with limit values that require monitoring at the workplace:****110-80-5 2-ethoxyethanol**

PEL	Long-term value: 740 mg/m ³ , 200 ppm Skin
REL	Long-term value: 1.8 mg/m ³ , 0.5 ppm Skin
TLV	Long-term value: 18 mg/m ³ , 5 ppm Skin; BEI

· **Ingredients with biological limit values:****110-80-5 2-ethoxyethanol**

BEI	100 mg/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: 2-Ethoxyacetic acid
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed goggles

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Colorless
Odor:	Ether-like
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	-90 °C (-130 °F)
Boiling point/Boiling range:	135 °C (275 °F)

· Flash point: 42 °C (107.6 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 235 °C (455 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Not determined.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	1.8 Vol %
Upper:	15.7 Vol %

· Vapor pressure at 20 °C (68 °F): ~5 hPa (~3.8 mm Hg)

· Density at 20 °C (68 °F): 0.93 g/cm³ (7.76085 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F):	2.07 mPas
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.00 %
	930.0 g/l / 7.76 lb/gal

Solids content: 0.0 %

· Other information: No further relevant information available.

10 Stability and reactivity

· Reactivity: No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

110-80-5 2-ethoxyethanol

Oral	LD50	3,000 mg/kg (rat)
Dermal	LD50	3,300 mg/kg (rabbit)
Inhalative	LC50/4 h	2,000 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

Substance is not listed.

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Assessment by list): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1171
· UN proper shipping name	
· DOT	Ethylene glycol monoethyl ether
· IMDG, IATA	ETHYLENE GLYCOL MONOETHYL ETHER
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 1171 ETHYLENE GLYCOL MONOETHYL ETHER, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· Section 355 (extremely hazardous substances):	
Substance is not listed.	
· Section 313 (Specific toxic chemical listings):	
Substance is listed.	
· TSCA (Toxic Substances Control Act):	
	ACTIVE
· Hazardous Air Pollutants	
Substance is not listed.	

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 7)

· **Proposition 65**· **Chemicals known to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is listed.

· **Chemicals known to cause developmental toxicity:**

Substance is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

Substance is not listed.

· **TLV (Threshold Limit Value)**

Substance is not listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **RTECS**

Substance is not listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **NFPA ratings (scale 0-4)**

Health = 0

Fire = 2

Reactivity = 0

· **HMIS ratings (scale 0-4)**

Health = *1

Fire = 2

Reactivity = 0

· **Department issuing SDS:** Technical Support Department· **Contact:** Technical Support Department· **Date of preparation / last revision** 07/09/2024 / -· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: 2-Ethoxyethanol

(Contd. of page 8)

*PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Repr. 1A: Reproductive toxicity – Category 1A*

US