

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

1 Identification

- **Product identifier**
- **Trade name:** μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution
- **Article number:** 215190
- **CAS Number:** 67719-69-1
- **Application of the substance / the mixture** Laboratory chemicals for research and development
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 BeanTown Chemical
 9 Sagamore Park Road
 Hudson, NH 03051
 USA

 Phone: (603) 402-2234
 Fax: (603) 402-9713
 Email: technical@beantownchem.com
www.beantownchem.com
- **Information department:** Technical Support Department
- **Emergency telephone number:**
 During normal operating hours, please call (603) 402-2234
 After hours, please call Chemtrec at (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Water-react. 2 H261 In contact with water releases flammable gas.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 1)

· Hazard pictograms

· Signal word *Danger*

· Hazard-determining components of labeling:

toluene

 μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum

· Hazard statements

Highly flammable liquid and vapor.

In contact with water releases flammable gas.

Causes severe skin burns and eye damage.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Do not allow contact with water.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: *Mixtures*

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

108-88-3	toluene	83.6%
67719-69-1	μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum	16.4%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Extinguishing powder. Do not use water.
CO₂. Do not use water.
Sand. Do not use water.
Special powder for metal fires. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

108-88-3	toluene	67 ppm
----------	---------	--------

· **PAC-2:**

108-88-3	toluene	560 ppm
----------	---------	---------

· **PAC-3:**

108-88-3	toluene	3700* ppm
----------	---------	-----------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 3)

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:**

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 20 ppm BEI, NIC-OTO

· **Ingredients with biological limit values:**

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 4)

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:**

Liquid

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition****Melting point/Melting range:**

Undetermined

Boiling point/Boiling range:

Undetermined

· **Flash point:**

4 °C (39.2 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

535 °C (995 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 5)

· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)
· Density at 20 °C (68 °F):	0.927 g/cm ³ (7.73582 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	83.6 %
VOC content:	83.60 %
	775.0 g/l / 6.47 lb/gal
Solids content:	16.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 6)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
----------	---------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA**

UN3399

· **UN proper shipping name**

· **DOT**

· **IMDG, IATA**

Organometallic substance, liquid, water-reactive, flammable

ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE,
FLAMMABLE

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 7)

· Transport hazard class(es)	
· DOT	
· Class	4.3 Substances which, in contact with water, emit flammable gases
· Label	4.3, 3
· IMDG	
· Class	4.3 Substances which, in contact with water, emit flammable gases
· Label	4.3/3
· IATA	
· Class	4.3 Substances which, in contact with water, emit flammable gases
· Label	4.3 (3)
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Substances which, in contact with water, emit flammable gases
· EMS Number:	F-G,S-M
· Stowage Category	D
· Stowage Code	SW2 Clear of living quarters.
· Handling Code	H1 Keep as dry as reasonably practicable
· Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.
	SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 3399 ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE, 4.3 (3), II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

· **TSCA (Toxic Substances Control Act):**

108-88-3 toluene

ACTIVE

· **Hazardous Air Pollutants**

108-88-3 toluene

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 8)

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

108-88-3 toluene

II

· **TLV (Threshold Limit Value)**

108-88-3 toluene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **RTECS**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **NFPA ratings (scale 0-4)**

Health = 3

Fire = 3

Reactivity = 2

The substance demonstrates unusual reactivity with water.

· **HMIS ratings (scale 0-4)**

Health = *3

Fire = 3

Reactivity = 2

· **Department issuing SDS:** Technical Support Department· **Contact:** Technical Support Department· **Date of preparation / last revision** 07/09/2024 / -· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/09/2024

Reviewed on 07/08/2024

Trade name: μ -Chloro- μ -methylenebis(cyclopentadienyl)titaniumdimethylaluminum solution

(Contd. of page 9)

*OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEL: Biological Exposure Limit**Flam. Liq. 2: Flammable liquids – Category 2**Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Repr. 2: Reproductive toxicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1*

US