Approval: _____

Customer Signature Required Upon Order

Customer Company Name: _____

1. Shell Side:
   - Max. Allowable Work Pressure: 600psi @ 250F
   - Min. Design Metal Temp.: -20F @ 600psi
   - Capacity: 2.02 ft3
   - Type of Fluid (Non-lethal): CFC, HFC, HCFC, OIL
   - Physical State of Fluid: LIQUID / VAPOR
   - Vessel Stamp: U

2. Tube Side:
   - Max. Allowable Work Pressure: 150psi @ 150F
   - Min. Design Metal Temp.: -20F @ 150psi
   - Capacity: 0.57 ft3
   - Type of Fluid (Non-lethal): WATER / ANTIFREEZE
   - Physical State of Fluid: LIQUID
   - Vessel Stamp: NON CODE

3. Manufacture vessel in accordance with ASME Sec VIII Div. 1 (Latest Version)
4. Pressure boundary parts are carbon steel / Tubes are copper.
5. All connections will be shipped with caps and plugs.
6. Vessel will be painted black.





NO	REVISIONS (INDICATED BY △)	BY	DATE
0	ORIGINAL	VRY	09/13/2013
1	UPDATE VESSEL LENGTH	AC	8/5/2017
2	update feet and nameplate	AC	11/1/2018
3			
4			
5			
6			

JOB#

MATERIAL

	NAME	DATE
DRAWN	VRY	09/13/2013
CHECK		
APVD		

TITLE: APPROVAL DRAWING

SIZE B | VESSEL NO. HPC050HS-XLX | REV 02

SCALE: 1:8 | SHIPPING WEIGHT: 318.39 lbs

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BITZER US. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT THE WRITTEN PERMISSION OF BITZER US IS PROHIBITED.

VIEW CONVENTION THIRD ANGLE

BREAK SHARP EDGES
THREADS TO BE CLASS 2
DIM & TOL PER ANSI Y14.5M

ANGULAR TOL ± 2°
FRAC TOL ± 1/4
1 INCH = 25.400000 MM

INCHES		METRIC (MM)	
.X	± .125	X.	± 1
.XX	± .063	X.X	± 0.5
.XXX	± .005	X.XX	± 0.25
		X.XXX	± 0.13