

AGRIMAX V - FLECTO



As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

MACHINERY

 AGRICULTURE

HIGH POWER TRACTOR

APPLICATIONS

 AGRICULTURE

FIELD AND ROAD TRANSPORT SOIL TILLAGE

PLUS



HIGH LOAD CAP
STANDARD PRESSURE



HIGH FLOTATION
CAPABILITY



REDUCED SOIL
COMPACTION



FUEL ECONOMY



TRACTION



REINFORCED BEAD



COMFORT



DURABILITY

PRODUCT: AGRIMAX V - FLECTO



TECHNICAL DATA U/M: US STANDARD (INCH)

Size	US Code	LI/SS	RIM REC	SW	OD	SLR	RC	Type	TMPH
VF 480/60 R 28 NRO	94060740	145 D	DW 16 L	18.5	50.8	22.5	149.9	TL	
VF 520/60 R 28 NRO	94060733	149 D	DW 18 L	20.3	52.6	23.1	153.9	TL	
VF 600/60 R 28 NRO	94058495	157 D	DW 20 B	23.1	56.7	24.9	166.5	TL	1
VF 600/60 R 30 NRO	94053360	158 D	DW 20 B	23.4	58.5	25.6	172.3	TL	
VF710/60 R 38 NRO	94058563	171 D	DW 25 B	27.9	71.7	31.3	212.4	TL	
VF 540/65 R38 NRO	94059119	162 D	DW 20 B	21.6	66.0	29.9	196.1	TL	1
VF 600/60 R 38 NRO	94059126	166 D	DW 20 B	23.1	66.3	29.8	198.6	TL	1
VF 650/65 R38 NRO	94059102	169 D	DW 23 B	25.6	71.9	31.4	212.1	TL	1
VF 710/60 R 42 NRO	94053377	173 D	DW 25 B	28.0	76.0	33.9	225.4	TL	