

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ: ЕДИНИЦЫ ИЗМЕРЕНИЯ: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TKPH
6.5/80 - 12			4	5 J	163	608	273	1851	TT	
6.5/80 - 12			4	5 J	163	608	273	1851	TL	
6.5/80 - 12			6	5 J	163	608	273	1851	TT	
6.5/80 - 12			6	5 J	163	608	273	1851	TL	
6.5/80 - 12	HD		6	5 J	163	608	273	1851	TT	0
7.00 - 12			4	4.5	187	683	300	2001	TT	
7.00 - 12			4	4.5	187	683	300	2001	TL	
7.00 - 12			6	4.5	187	683	300	2001	TL	0
7.00 - 12			6	4.5	187	683	300	2001	TT	1
7.00 - 12	ARAMID BELTED		8	4.5	187	683	300	2001	TL	
7.00 - 12	SPECIAL		8	4.5	187	683	300	2001	TL	
10.0/80 - 12			10	9.00	270	730	335	2233	TL	
11.0/65 - 12			8	9.00	273	700	321	2072	TT	
11.0/65 - 12			8	9.00	273	700	321	2072	TL	
26 X 12.00 - 12		112 A6		10.50 AT	310	648	298	1932	TL	
5.00 - 15			4	3.50 D	140	657	308	1957	TT	
5.00 - 15			6	3.50 D	140	657	308	1957	TT	
5.00 - 15			6	3.50 D	140	657	308	1957	TL	
7.5L - 15			6	6 LB	210	765	354	2280	TT	
7.5L - 15			8	6 LB	210	765	354	2280	TT	
7.5L - 15			8	6 LB	210	765	354	2280	TL	
7.5L - 15	ARAMID BELTED HD		8	6 LB	210	765	354	2280	TL	
7.5L - 15	HD		8	6 LB	210	765	354	2280	TT	
400/50 - 15				13 LB	395	790	369	2387	TL	
10.0/75 - 15.3			8	9.00	264	780	345	2285	TT	
10.0/75 - 15.3			8	9.00	264	780	345	2285	TL	
10.0/75 - 15.3	INDUSTRIAL		8	9.00	264	780	345	2285	TL	
10.0/75 - 15.3			10	9.00	264	780	345	2285	TL	
10.0/75 - 15.3			14	9.00	264	780	345	2285	TL	
10.0/75 - 15.3			18	9.00	264	780	345	2285	TT	
10.0/75 - 15.3			18	9.00	264	780	345	2285	TL	
11.5/80 - 15.3			8	9.00	290	867	380	2540	TT	
11.5/80 - 15.3			8	9.00	290	867	380	2540	TL	
11.5/80 - 15.3			10	9.00	290	867	380	2540	TL	
11.5/80 - 15.3			12	9.00	290	867	380	2540	TT	
11.5/80 - 15.3			12	9.00	290	867	380	2540	TL	
11.5/80 - 15.3	STUBBLE RESISTANT		12	9.00	290	867	380	2540	TL	
11.5/80 - 15.3			14	9.00	290	867	380	2540	TT	
11.5/80 - 15.3			14	9.00	290	867	380	2540	TL	
27 X 10 - 15.3			8	9.00	260	695	317	2071	TT	
27 X 10 - 15.3			8	9.00	260	695	317	2071	TL	
4.00 - 16			4	3.00 D	110	628	0	0	TT	
6.00 - 16			6	4.00 E	164	735	343	2190	TT	0
6.00 - 16	HD		6	4.00 E	164	735	343	2190	TT	
6.00 - 16	HD		8	4.00 E	164	735	343	2190	TT	

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ: ЕДИНИЦЫ ИЗМЕРЕНИЯ: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TKPH
7.50 - 16			6	5.50 F	209	803	372	2393	TT	
7.50 - 16			8	5.50 F	209	803	372	2393	TT	
7.50 - 16			8	5.50 F	209	803	372	2393	TL	
7.50 - 16	HD		8	5.50 F	209	803	372	2393	TT	
9.0/70 - 16			10	W 7	222	760	355	2285	TL	
270/75 - 16				9.00	250	810	0	0	TL	
15.0/55 - 17			10	13.00	380	890	395	2608	TL	
15.0/55 - 17			14	13.00	380	890	395	2608	TL	
19.0/45 - 17			14	16.00	465	865	389	2578	TL	
420/55 - 17			14	13.00	430	910	407	2712	TL	
420/55 - 17			16	13.00	430	910	407	2712	TL	
7.50 - 18			6	5.50 F	209	854	407	2649	TT	
7.50 - 18			8	5.50 F	209	854	407	2649	TT	
10.5/80 - 18			10	W 9	274	907	405	2657	TL	
12.5/80 - 18			12	W 9	308	987	438	2892	TL	
12.5/80 - 18	SPECIAL		12	W 9	308	987	438	2892	TL	
12.5/80 - 18			16	W 9	308	987	438	2892	TL	
12.5/80 - 18			18	W 9	308	987	438	2892	TL	
7.50 - 20			8	5.50 F	209	904	422	2695	TT	
16.0/70 - 20			10	13	408	1097	487	3214	TL	
16.0/70 - 20			12	13	408	1097	487	3214	TL	
16.0/70 - 20			14	13	408	1097	487	3214	TL	
16.0/70 - 20			16	13	408	1097	487	3214	TL	
400/70 - 20	INDUSTRIAL	149 A8		13	408	1097	487	3214	TL	
15.5/80 - 24			10	W 12	384	1262	566	3655	TL	
15.5/80 - 24			12	W 12	384	1262	566	3655	TL	
15.5/80 - 24			14	W 12	384	1262	566	3655	TL	
15.5/80 - 24	SPECIAL		14	W 12	384	1262	566	3655	TL	
15.5/80 - 24			16	W 12	384	1262	566	3655	TL	
16.5/85 - 24			10	W 13	415	1325	591	3837	TL	
16.5/85 - 24			12	W 13	415	1325	591	3837	TL	
16.5/85 - 24			16	W 13	415	1325	591	3837	TT	
16.5/85 - 24			16	W 13	415	1325	591	3837	TL	
400/80 - 24	INDUSTRIAL	156 A8		W 13	394	1262	566	3655	TL	
400/80 - 24	INDUSTRIAL	162 A8		W 13	394	1262	566	3655	TL	0