

LumiView™ Cool Light Fiber Optic Retractor System



Ergonomic handle
for a comfortable and firm grip

Angled tip for
atraumatic retraction

full blade illumination for
optimal surgical viewing

High intensity fiber
optic molded light panel
never gets hot

Light panel delivers
cool, directional,
uniform light

Interchangeable
blade design

Various sized blades and light panels used with one
retractor handle provide economy and diversity
for a wide range of procedures



 **BLACK & BLACK**
S U R G I C A L

LumiView™ Cool Light Fiber Optic Retractor System

The LumiView™ Cool Light Fiber Optic Retractor System converts traditionally hot Xenon and Halogen light into cool, directional, uniform illumination. The LumiView™ retractor incorporates a unique quick-change blade design allowing for multiple blades to be used with one light guide handle. The single-use light panels deliver uniform, cool lighting even into the most difficult areas.

HANDLES



Retractor Handles with Fiber Optic Light Guide

The ergonomically designed handle enhances maneuverability and accelerates the ability to capture deep pocket visualization.

- B 61104 Small LumiView™ Retractor Handle with Light Guide
- B 61105 Standard LumiView™ Retractor Handle with Light Guide
- B 61107 Replacement Light Guide for LumiView™ Retractor for Handle B 61105
- B 61108 Replacement Light Guide for LumiView™ Retractor for Handle B 61104



LIGHT PANELS



Single Use Lumiview Light Panels

- B 61100 "Mini" Light Panel, 5/Box, Sterile
- B 61101 "Midi" Light Panel, 5/Box, Sterile

BLADES



"Mini" LumiView™ Retractor Blades

- * B 61110 1/2" (12.5 mm) x 4" (10 cm)
- B 61111 3/4" (20 mm) x 4" (10 cm)
- B 61112 1" (24 mm) x 4" (10 cm)

"Mini" LumiView™ Retractor Blades with Suction

- B 61111S 3/4" (20 mm) x 4" (10 cm) with Suction
- B 61112S 1" (24 mm) x 4" (10 cm) with Suction

"Mini" LumiView™ Aluminum Retractor Blades

- B 61111AL 3/4" (20 mm) x 4" (10 cm)
- B 61112AL 1" (24 mm) x 4" (10 cm)
- B 61113AL 1-1/4" (30 mm) x 4" (10 cm)
- B 61120AL 1" (24 mm) x 5 3/8" (13.5 cm)

"Midi" LumiView™ Retractor Blades

- * B 61115 1/2" (12.5 mm) x 5-3/8" (13.5 cm)
- B 61116 3/4" (20 mm) x 5-3/8" (13.5 cm)
- B 61120 1" (24 mm) x 5-3/8" (13.5 cm)
- B 61121 1-1/4" (30 mm) x 5-3/8" (13.5 cm)
- B 61125 3/4" (20 mm) x 7" (17.5 cm)
- B 61126 1-1/4" (30 mm) x 7" (17.5 cm)

"Midi" LumiView™ Retractor Blades with Suction

- B 61116S 3/4" (20 mm) x 5-3/8" (13.5 cm) with Suction
- B 61120S 1" (24 mm) x 5 3/8" (13.5 cm) with Suction
- B 61121S 1-1/4" (30 mm) x 5-3/8" (13.5 cm) with Suction
- B 61125S 3/4" (20 mm) x 7" (17.5 cm) with Suction
- B 61126S 1-1/4" (30 mm) x 7" (17.5 cm) with Suction

"Midi" LumiView™ Aluminum Retractor Blades

- B 61120AL 1" (24 mm) x 5-3/8" (13.5 cm)
- B 61121AL 1-1/4" (30 mm) x 5-3/8" (13.5 cm)
- B 61126AL 1-1/4" (30 mm) x 7" (17.5 cm)

* 1/2" (12.5mm) blades have rounded tips

LIGHT SOURCES



Onyx-Lite; 50-Watt Solid State LED Light Source

A compact, efficient, durable "daylight" light. Typical LED life of greater than 50,000 hours.

- B 78726 50-Watt Light Source with 4-Port Turret



XS-300; 300-Watt Xenon Light Source

Provides superior illumination for unparalleled visualization of the surgical field. A field replaceable xenon bulb reduces unwanted downtime and maintenance delays.

- B 78730 300-Watt Xenon Light Source with 4-Port Turret
- B 78731 Lamp Replacement, XS-300
- B 78720 Mobile Stand for XS-300, Tip Resistant

Fiber Optic Cables

Cables are steam autoclavable and feature clear, silicone housing for easy viewing of damaged fiber optic strands.

- B 79722 Storz/Storz, 5 mm x 9'
- B 79725 Storz/Storz, 5 mm x 7.5'
- B 79727 ACMI/ACMI, 5 mm x 7.5'
- B 79765 ACMI/ACMI, 5 mm x 9'

ORDERING INFO:

1. Choose Handle
2. Choose Retractor Blade
3. Choose Light Panel
4. Choose Fiber Optic Cable