BMW Media information

07/2012 Page 31

## BMW 3 Series Touring.

328i.

		BMW 328i Touring
Body		
No of doors / seats		5/5
Length/width/height (unladen)	mm	4624 / 1811 / 1429
Wheelbase	mm	2810
Track, front/rear	mm	1531 / 1572
Ground clearance		140
Turning circle	m	11,3
Tank capacity		60
Cooling system incl heater	ltr	6,9 (7,6)
Engine oil <sup>1)</sup>	ltr	5,75
Weight, unladen, to DIN/EU	kg	1500 / 1585 (1520/1595)
Max load to DIN	kg	550
Max permissible	kg	2050 (2070)
Max axle load, front / rear	kg	915 / 1210
Max trailer load (12%), braked / unbraked	kg	1600 / 745
Max roofload / max download	kg	75 / 75
Luggage comp	ltr	495 / 1500
Air drag	cd x A	0,32 x 2,20
Power Unit		
Configuration/No of cyls/valves		In line / -4 / 4
Engine technology		BMW TwinPower Turbo, second-generation direct fuel injection (High Precision Injection), fully variable valve management (VALVETRONIC)
Capacity, effective	CC	1997
Stroke / bore	mm	90,1 / 84,0
Compression ratio	:1	10,0
Fuel		min RON 91
Max output	kW/hp	180 / 245
at	rpm	5000-6000
Max torque	Nm/lb-ft	350
<u>at</u>	rpm	1250-4800
Electrical System		
Battery / installation	Ah/–	90 / Luggage Compartment
Alternator	AW	210 / 2940
Driving Dynamics and Safe	ty	Double in the same about only in all mainings with displaced and appear and linear
Suspension, front		Double-joint spring strut axle in aluminium with displaced castor, small positive steering roll radius, compensation of lateral forces, anti-dive
Suspension, rear		Five-arm axle in lightweight steel
Brakes, front		Single-piston swing-calliper disc brakes/ vented
Brakes, rear		Single-piston swing-calliper disc brakes/ vented
Driving stability systems		Standard: DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Brake Assistant, Dry Braking, Fading Compensation, Start-Off Assistant
Safety		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel belts on all seats, with belt retainer, belt latch tensioner and belt force limiter at the front, crash-activated headrests at the front, crash sensors, Tyre Defect Indicator
Steering		Electric Power Steering
Steering ratio, overall	:1	15,1
Tyres, front/rear		225/50 R17 94W
Wheels, front/rear		7,5J x 17 Light Alloy

			BMW 328i Touring
BMW Conne	t - dD.::		
	ecteaprive		Outlined DNAMA Assisting discounting and in contract
Comfort			Optional: BMW Assist including information service, remote functions Real-Time Traffic Information, BMW TeleServices, mobile device integration
Infotainment			Optional: access to the internet, BMW Online incl Parkinfo, National Info
		Google directory search, news, realtime weather, BMW Routes, office functions	
		Bluetooth audio streaming and music title update online, apps	
Safety			Optional: Adaptive Headlights with turning lights, variable light distribution and adaptive headlight range adjustment, high beam assistance, park distance control, rear view camera, Surround View incl. Side View and Top View BMW Head-Up Display, cruise control with brake function, Parking Assistant Lane Chance Warning, Lane Departure Warning with Collision Warning, speec limit and no passing information, Active Protection, extended emergency cal
Transmissis			
Transmissio			
Type of trans			Six-speed manual (optional: eight-speed automatic)
Gear ratios	I	:1	3,683 (4,174)
	<u> </u>	:1	2,062 (3,143)
	 	:1	1,313 (2,106)
	IV	:1	1,000 (1,667)
	V VI	:1	0,809 (1,285)
		:1	0,677 (1,000)
	VII	:1	(0,839)
	R	:1 :1	(0,667) 3,348 (3,295)
Final Drive	R	:1	3,909 (3,154)
			3,000 (0).10.1
Performanc			0.0 (0.4)
Power-to-wei		kg/kW	8,3 (8,4)
Output per lite		kW/hp	90,1
Acceleration		sec	6,0 (6,0)
L. Alle/Ellere	standing-start	sec	26,0 (25,9)
Top speed	ar80–120 km/h	sec km/h	5,8 / 7,2 (-' 250 (250)
rop speed		KITI/II	250 (250,
BMW Efficie	entDynamics		
BMW Efficien	ntDynamics,		Brake Energy Regeneration, electromechanical power steering, Automatic
standard feat	ures		Start/Stop function, gear shift indicator (manual), ECO PRO mode, intelligent lightweight construction, on-demand operation of ancillary units, map-regulated oil pump, air flap control, Electric Power Steering (EPS), detachable ale compressor, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance
Fuel Consu	mp in EU Cycle		
Urban		ltr/100k	9,2 (8,4)
Extra-urban		ltr/100k	5,5 (5,4)
Combined		ltr/100k	6,8 (6,5)
CO <sub>2</sub>		g/km	159 (152)
Emission ratir			EU5

Specifications apply to ACEA markets/data relevant to homologation apply in part only to Germany (weight) Figures in brackets apply to models with automatic transmission

<sup>1)</sup> Oil change