

# BMW

## U.S. Media Information

### Contacts:

Thomas Plucinsky  
Product & Technology Communications Manager  
201-307-3783 / thomas.plucinsky@bmwna.com

David J. Buchko  
Advanced Powertrain & Heritage Communications  
201-307-3709 / dave.buchko@bmwna.com

Matthew Russell  
BMW Product & Technology Communications  
Tel. 201-307-3755  
Matthew.Russell@bmwna.com

## Technical Data.

### 2011 BMW M3 Convertible.

		M3 Convertible Manual 6 Speed	M3 Convertible DCT 7 Speed
<b>10.01.2010</b>			
<b>Body</b>			
No. of Doors / Seating Capacity	-	2 / 4	2 / 4
Vehicle Length	mm / inch	4618 / 181.8	4618 / 181.8
Vehicle Width	mm / inch	1804 / 71	1804 / 71
Vehicle Height, Unloaded	mm / inch	1392 / 54.8	1392 / 54.8
Wheelbase	mm / inch	2761 / 108.7	2761 / 108.7
Turning Circle	m / ft	11.7 / 38.4	11.7 / 38.4
Track, Front	mm / inch	1540 / 60.6	1540 / 60.6
Track, Rear	mm / inch	1539 / 60.6	1539 / 60.6
Width at Shoulderheight, Front	mm / inch	1404 / 55.3	1404 / 55.3
Width at Shoulderheight, Rear	mm / inch	1251 / 49.3	1251 / 49.3
Effective Leg Room, Front	mm / inch	1068 / 42	1068 / 42
Effective Leg Room, Rear	mm / inch	814 / 32	814 / 32
Effective Head Room, Front	mm / inch	965 / 38	965 / 38
Effective Head Room, Rear	mm / inch	927 / 36.5	927 / 36.5
Trunk Volume acc SAE1100	ft <sup>3</sup>	9	9
Fuel Capacity	L / gal	63 / 16.6	63 / 16.6
Curb Weight	kg / lbs	1880 / 4145	1880 / 4145
Weight Distribution, Front / Rear	%	47.2 / 52.8	47.2 / 52.8
Gross Vehicle Weight Rating (GVWR)	kg / lbs	2280 / 5027	2280 / 5027
Payload	kg / lbs	400 / 822	400 / 822
Axle Load Limit, front	kg / lbs	1010 / 2227	1010 / 2227
Axle Load Limit, rear	kg / lbs	1200 / 2646	1200 / 2646
Towing Capacity	kg / lbs	- / -	- / -
Roof Load Limit	kg / lbs	- / -	- / -
Drag Coefficient	Cd	0.32	0.32
Drag Cd x A	m <sup>2</sup> / ft <sup>2</sup>	0.69 / 7.47	0.69 / 7.47
<b>Engine</b>			
		S65B40	S65B40
Engine Type / Cylinder / Valves per Cylinder	-	V 90 / 8 / 4 VANOS	V 90 / 8 / 4 VANOS
Engine Management System	-	BMW MS S60 Port Injection	BMW MS S60 Port Injection
Induction System		Natural, tuned runners	Natural, tuned runners
Displacement	cm <sup>3</sup> / inch <sup>3</sup>	3999 / 244	3999 / 244
Stroke	mm / inch	75.2 / 2.96	75.2 / 2.96
Bore	mm / inch	92 / 3.62	92 / 3.62
Power	SAE hp / rpm	414 / 8300	414 / 8300
Torque	ft lbs / rpm	295 / 3900	295 / 3900
Compression Ratio / Fuel type	-	12 / Premium	12 / Premium
<b>Chassis and Suspension</b>			
Codification of Reference Gearbox	-	G	M DKG 436
Gear Ratios	I	4.055	4.780
	I	2.396	2.933
	II	1.582	2.153
	IV	1.192	1.678
	V	1.000	1.390
	V	0.872	1.203
	VI	-	1.000
Reverse Ratio	-	3.677	4.454
Final Drive Ratio	-	3.846	3.154
Steering Type / Ratio	-	Rack-and-pinion / 12.5	Rack-and-pinion / 12.5
Front Brakes / Diameter	- / mm / inch	Vent. Disc / 360 / 14.2	Vent. Disc / 360 / 14.2
Rear Brakes / Diameter	- / mm / inch	Vent. Disc / 350 / 13.8	Vent. Disc / 350 / 13.8
Tire Type, Front	-	245/40 ZR18	245/40 ZR18
Tire Type, Rear	-	265/40 ZR18	265/40 ZR18
Wheels, Front	-	8.5J x 18 Light alloy	8.5J x 18 Light alloy
Wheels, Rear	-	9.5J x 18 Light alloy	9.5J x 18 Light alloy
<b>Performance</b>			
Top Speed	km/h / mph	250 / 155	250 / 155
Top Speed w. Sport Package	km/h / mph	- / -	- / -
Acceleration, 0-60 mph	s	5.1	4.9
Acceleration, 0-100 Km/h	s	5.3	5.1
Fuel Economy, EPA Estimate - City	mpg	13	14
Fuel Economy, EPA Estimate - Highway	mpg	20	20
Fuel Economy, EPA Estimate - Combined	mpg	16	16
Approximate Range	km / miles	430 / 270	430 / 270