

BMW

U.S. Media Information

Contacts:

Thomas Plucinsky
Product & Technology Communications Manager
201-307-3783 / thomas.plucinsky@bmwna.com

David J. Buchko
Advanced Powertrain & Heritage Communications
201-307-3709 / dave.buchko@bmwna.com

Monty Roberts
BMW Product & Technology Communications
Tel. 201-307-3755
Monty.Roberts@bmwna.com

Technical Data.

2012 BMW ActiveHybrid 7.

	ActiveHybrid 7 Sedan Hybrid Auto 8 Speed	ActiveHybrid 7 L Sedan Hybrid Auto 8 Speed
11.01.2011		
Body		
No. of Doors / Seating Capacity	-	4 / 5
Vehicle Length	mm / inch	5074 / 199.8
Vehicle Width	mm / inch	1902 / 74.9
Vehicle Height, Unloaded	mm / inch	1485 / 58.5
Wheelbase	mm / inch	3070 / 120.9
Turning Circle	m / ft	12.5 / 41.0
Track, Front	mm / inch	1621 / 63.8
Track, Rear	mm / inch	1632 / 64.3
Ground Clearance	mm / inch	151 / 5.94
Width at Shoulderheight, Front	mm / inch	1503 / 59.2
Width at Shoulderheight, Rear	mm / inch	1458 / 57.4
Effective Leg Room, Front	mm / inch	1048 / 41.3
Effective Leg Room, Rear	mm / inch	987 / 38.9
Effective Head Room, Front	mm / inch	1032 / 40.6
Effective Head Room, Rear	mm / inch	978 / 38.5
Trunk Volume acc SAE1100	ft³	13
Fuel Capacity	L / gal	80 / 21.1
Curb Weight	kg / lbs	2175 / 4795
Weight Distribution, Front / Rear	%	51.3 / 48.7
Gross Vehicle Weight Rating (GVWR)	kg / lbs	2640 / 5820
Payload	kg / lbs	460 / 1014
Axle Load Limit, front	kg / lbs	1310 / 2888
Axle Load Limit, rear	kg / lbs	1430 / 3153
Towing Capacity	kg / lbs	- / -
Roof Load Limit	kg / lbs	100 / 220
Drag Coefficient	Cd	0.31
Drag Cd x A	m² / ft²	0.75 / 8.07
Engine		
Engine Type / Cylinder / Valves per Cylinder	-	V 90 / 8 / 4 VANOS
Engine Management System	-	MSD85 Direct Injection
Induction System	-	twin turbo reverse flow "hot V"
Boost Pressure / Overboost	Bar	0.6
Displacement	cm³ / inch³	4395 / 268.2
Stroke	mm / inch	88.3 / 3.48
Bore	mm / inch	89 / 3.50
Power	SAE hp / rpm	440 / 5500-6400
Torque	ft lbs / rpm	480 / 1800-4500
Compression Ratio / Fuel type	-	10.0 / Premium
Nominal Power Output w. eBoost	SAE hp / rpm	455 / 5500-6000
Max. Torque w. eBoost	ft lbs / rpm	515 / 2000-3000
Chassis and Suspension		
Codification of Reference Gearbox	-	Hybrid 8HP70H
Gear Ratios	I	4.714
	II	3.143
	III	2.106
	IV	1.667
	V	1.285
	VI	1.000
	VII	0.839
	VIII	0.667
Reverse Ratio	-	3.317
Final Drive Ratio	-	2.810
Steering Type / Ratio	-	Rack-and-pinion / 19.1
Front Brakes / Diameter	- / mm / inch	Vent. Disc / 374 / 14.7
Rear Brakes / Diameter	- / mm / inch	Vent. Disc / 370 / 14.6
Tire Type, Front	-	245/45 R19 98Y RSC AS
Tire Type, Rear	-	275/40 R19 101Y RSC AS
Wheels, Front	-	8.5J x 19 Light alloy
Wheels, Rear	-	9.5J x 19 Light alloy
Performance		
Top Speed	km/h / mph	240 / 150
Top Speed w. Sport Package	km/h / mph	240 / 150
Acceleration, 0-60 mph	s	4.7
Acceleration, 0-100 Km/h	s	5.1
Fuel Economy, EPA Estimate - City	mpg	17
Fuel Economy, EPA Estimate - Highway	mpg	24
Fuel Economy, EPA Estimate - Combined	mpg	20
Approximate Range	km / miles	680 / 425