

Professional Grade
SURFACE
Odor Counteractant

FORMULA

#2000oc

Contains Airicide®

AIRx[®]

ODOR CONTROL "WAX" STRIPPER

For Hospitals, Nursing Homes,
Food Areas, Etc.



RX2000 Odor Controlled Floor Finish stripper was formulated to have an extremely low odor while retaining all of the qualities you would expect from a modern stripper. Ideal for use with its companion product, RX2002 Odor Controlled Floor Finish in areas or facilities where these qualities would be a particular advantage. RX2000 also stays wet longer than traditional strippers allowing the job to be accomplished with less labor and time.

RX2000 was originally formulated to be a companion product to RX2002 Odor Controlled Floor Finish but will work on other zinc interlocked finishes as well. RX2000 is a departure from traditional strippers because of its extremely low odor while retaining all of its ability to remove the toughest of finishes.

Description

A more effective stripper because it is formulated to remain wet on the floor longer. With longer dwell time, finishes can be re-emulsified with less work and less product. Its unique low odor formula allows it to be used in many facilities where a low odor product is desired or even required.

Uses

Designed to strip all types of floor finishes from both resilient and non-resilient floors. RX2000 has a particular advantage over most other strippers because of its stay wet, odor controlled formulation. Ideal for use with its companion product, RX2002 Odor Control Floor Finish. Although it can be used in any area or facility, it is particularly useful in hospitals, clinics, doctor's offices, nursing homes, hospice centers, or anywhere a low odor formulation is needed.





ODOR CONTROL "WAX" STRIPPER

For Hospitals, Nursing Homes,
Food Areas, Etc.



Benefits

- Odor controlled, stay wet formula
- Less labor
- Can be used with or without a floor machine
- Can be used in conjunction with its companion product, RX2002 Odor Controlled Floor Finish
- Butyl free

Directions

FOR STRIPPING WITHOUT A MACHINE - Dilute 1 part
stripper with 4-6 parts water (approx. 20-32oz. per gal).

1. Wet section of floor with solution and allow to soak about 10 minutes.
2. Agitate with mop and allow stripper to work another 10 minutes.
3. Pick up solution or squeegee it to another section.
4. Do not allow residue to dry on the floor. Rinse it off with clear water while still wet.
5. When floor is dry, apply AIRX Stain proof Sealer and/or AIRX Finish.

FOR STRIPPING WITH A MACHINE - Dilute 1 part stripper with 12-16 parts water (approx. 8-12oz. per gal).

1. Wet section of floor with solution and allow to soak for 10 minutes.
2. Agitate with a machine equipped with a stripping pad.
3. Pick up solution or squeegee it to another section.
4. Do not allow residue to dry on the floor. While still wet rinse it off with clear water.
5. When floor is dry apply AIRX Stain proof sealer and/or AIRX Finish.

Specifications

APPEARANCE.....Liquid
ODOR.....Relatively odorless
pH.....12.0
WATER SOLUBILITY.....Complete
SPECIFIC GRAVITY.....1.030
FLASH POINT.....> 167°F
BOILING POINT.....Apprx. 212°F

Distributed by:

