



22 KARAT

Great Gloss & Durable Floor Finish

DESCRIPTION

The right product for beautiful, safe floors requiring minimum maintenance. This modern blend of clear acrylic polymers is easy to apply and dries to a high gloss without polishing. Resists black marks and scuffing, resists tracked in water and is not harmed by surface cleaning with detergents, but can be removed easily when desired.

BENEFITS

MORE DURABLE: Other finishes may not literally wear through, but they pick up dirt and black marks, become badly scuffed and discolor necessitating stripping and recoating. 22 Karat stays clean and clear.

HIGH GLOSS: Dries to a high gloss without polishing and is an excellent base for spray buffing to a brilliant, mirror-like finish.

WATER RESISTANT: Resistant to spills and to water tracked on floors during bad weather.

DETERGENT RESISTANT: Floors maintained with 22 Karat can be mopped or even scrubbed with a mild detergent solution without removing the finish or harming its gloss.

EASILY REMOVED: In spite of its resistance to water and detergents, 22 Karat can be easily removed with its companion stripper when desired.

VERSATILE: May be used on vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non resilient floors.

HOW TO USE

PREPARATION: May be applied over other hard, non-wax floor finishes if they are clean and in good condition, but for best results we suggest at least top stripping with our companion stripper. Then rinse thoroughly and allow floor to dry.

APPLICATION: Apply a thin uniform coat in a figure eight motion using a clean finish mop or applicator. Avoid contact with finish as it dries. Allow each coat to dry 20-30 minutes before applying the next coat or walking on the floor. **NOTE:** Humid conditions may require longer drying times between coats.

MAINTENANCE: Dust and wet mopping will keep floors bright and shiny. When under heavy traffic, if the floor becomes dull, this finish is an excellent base for spray buffing.



SPECIFICATIONS

APPEARANCE.....	Milky liquid
SOLIDS CONTENT.....	22.0 ± 0.5%
ODOR.....	Characteristic floor finish
SPECIFIC GRAVITY.....	1.020 ± 0.005
DENSITY.....	8.51 ± 0.05 lb/gal
BOILING POINT.....	Near 212°F
pH.....	8.5 ± 0.5
FLASH POINT.....	None to boiling
STABILITY.....	One year minimum

PRODUCT CODE.....22K