



PRO-STRIP

Professional Heavy Duty Floor Stripper

DESCRIPTION

Pro-Strip is preferred by professional cleaners and cleaning contractors because it acts so quickly to re-emulsify build-up of all brands of old, oxidized, polymer, acrylic, metal interlock and wax floor finish.

BENEFITS

WORKS QUICKLY - Starts immediately to penetrate, soften and re-emulsify all brands of floor polish for easy, complete removal.

LOW ODOR - No ammonia or other unpleasant odors to bother occupants or cleaning personnel.

OPTIMUM STRENGTH - A strong solution of Pro-Strip is better for the floor than over-wetting with a weaker product that may run under and “pop” the tiles.

ECONOMICAL - Maintains its strength as it strips and can be squeegeed to a new area with continuing effectiveness. Dilute up to 8 ounces per gallon of water for use with floor machines.

HOW TO USE

The dilution of Pro-Strip needed depends on the buildup and the aging of the wax or finish to be removed.

DILUTIONS

LIGHT BUILD-UP: 8 oz/1/2 pint per gallon warm water

MEDIUM BUILD-UP: 16 oz/1 pint per gallon warm water.

HEAVY BUILD-UP: 24 oz/1-1/2 pint per gallon warm water.

DIRECTIONS

On old floors, such as asphalt tile, test dilute solution on an out of the way spot to assure stripper will not “bleed” or otherwise affect flooring material.

1. Apply solution liberally to cover a work space of about 100 square feet. Apply liberally but not so heavily to run into puddles or run under tiles...
2. Allow about 5 minutes for solution to penetrate. DO NOT ALLOW SOLUTION TO DRY...
3. Machine scrub with a synthetic stripping pad...
4. Pick up dirty solution with wet vac or mop...
5. Rinse area with clear water.



SPECIFICATIONS

APPEARANCE.....	Liquid
ODOR.....	Butyl
SPECIFIC GRAVITY.....	1.015 ± 0.005
DENSITY.....	8.47 ± 0.05 lb/gal
BOILING POINT.....	Near 212°F
pH.....	13.5 ± 0.5
FLASH POINT.....	None to boiling
STABILITY.....	One year minimum

PRODUCT CODE.....C435