



# DIAMOND COAT

High Gloss, Non-Dulling Floor Finish

## DESCRIPTION

This finish dries to a hard, non-scuff, long wearing film that does not require a floor machine for its maintenance. It dries to a gloss without need for polishing and resists scuffing and black marking to maintain it's gloss without the need for buffing. Although it does not require polishing, it is an excellent base for spray buffing.

## BENEFITS

**HARD, TOUGH, LONG-LASTING FILM:** Resists scuffing, black marks and imbedding of soil that leads to the need for stripping of other finishes.

**ATTRACTIVE GLOSS:** Dries to a high gloss without polishing and maintains that gloss without polishing.

**EASY APPLICATION:** Each new coat levels beautifully with the previous one, without bubbles, streaks or mop drag.

**CLEAR & COLORLESS:** Dries to a glass-like clarity that intensifies the natural colors in the floor, not discolor them.

**WATER RESISTANT:** To water based spills and to water tracked on floors during bad weather.

**VERSATILE:** May be used on vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non resilient floors.

## HOW TO USE

**FLOOR PREPARATION** - If floor needs stripping, use our companion stripper as directed. If floor is in good condition it need only be thoroughly clean and dry.

**APPLICATION** - 1. Apply a thin uniform coat in a figure eight motion using a clean finish mop or applicator. 2. On newly stripped floors, several coats may be required for desired gloss. On extremely porous floors, apply floor sealer to fill pours. Allow ample drying time between coats.

**MAINTENANCE** - 1. Dust mop all floors daily. 2. Damp mop using a neutral cleaner. 3. Spray Buffing: Floor must have several coats of finish to provide a good base. Spray buffing will increase gloss and durability. 4. Burnishing: Optimum gloss and durability can be achieved by burnishing with a high speed machine. A good base coat is required.



## SPECIFICATIONS

APPEARANCE.....	Milky liquid
SOLIDS CONTENT.....	19 ± 0.5%
ODOR.....	Characteristic floor finish
SPECIFIC GRAVITY.....	1.020 ± 0.005
DENSITY.....	8.51 ± 0.05 lb/gal
BOILING POINT.....	Near 212°F
pH.....	8.5 ± 0.5
FLASH POINT.....	None to boiling
STABILITY.....	One year minimum

PRODUCT CODE.....C490