

Specifications

Dimensions	23 ft. (7.01 m) long x 8 ft. 6 in. (2.59 m) wide x 8 ft. 7 in. (2.62 m) high
Weight	18,900 lb. (8572.90 kg)
Capacity	8,050 gal. (30,472.56 l) (nominal)
Valves	Two 4 in. (10.16 cm) butterfly valve drains with NPT threads, one at each end in recessed sumps
Manways	36" & 22" (91.44 cm & 55.88 cm) Combo side-entry ground-level manway
Inspection Hatch	Two 22 in. (55.88 cm) top inspection hatch with safety bars
Vent	8 in. (20.32 cm) vent/hatch equipped with pressure relief valve; 16 oz. psi (453.59 g psi) for pressure, 0.4 oz. psi (11.34 g psi) for vacuum
Roll-Off Structure	6 in. (15.24 cm) x 2 in. (5.08 cm) x 1/4 in. (0.635 cm) Rails; 36 in. (91.44 cm) Inside Dimension
Other Connections	Additional 4 in. (10.16 cm) and 2 in. (5.08 cm) NPT connections with caps

Options & Accessories

- Secondary Containment
- Camlock-Style Fittings
- Suction and Discharge Hoses
- Level Gauges
- Spillguard

Specifications are approximate and may vary. Ask your sales representative for specific dimensions for the unit we supply to you.

