



WELD #2 - COPPER

WELD THROUGH COPPER RICH BUILD PRIMER

Ready to Use

Description and Benefits

WELD #2 - COPPER is a high adhesion, super-conductive Copper rich Weld Through Primer specially formulated to offer excellent rust protection for both SPOT, MIG and TIG welding.

WELD #2 - COPPER contains high purity Copper giving excellent conductivity as well as high adhesion to metals.

WELD #2 - COPPER gives a durable, semi-flexible metallic finish, which leaves a corrosion resistant surface.

Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Surface preparation and instructions for use

Before applying **WELD #2 - COPPER**, Thoroughly clean and degrease surfaces with a suitable spirit wipe or thinner. Abrade the surfaces wet or dry with 280-320 abrasive, re-clean, dry and degrease.

Application

Shake can thoroughly before use for a minimum of 2 minutes.

Apply 1-2 light, even coats.

Allow 5-10 minutes flash-off time between coats.

Drying time

Allow 10-20 minutes before welding.

Drying time is dependent upon film thickness, humidity and temperature.

Welding using SPOT, MIG or TIG techniques should then be undertaken. For optimum anticorrosive protection, a second coat of **WELD #2 - COPPER** should be applied after welding is completed following the procedure described above.

Over-painting

WELD #2 - COPPER should be flatted wet with 600-800 or dry with 400-600 abrasive.

WELD #2 - COPPER may be over-painted with most paint systems.

VOC Information

MIR Ref. WTP: MIR 0.98

Product Code

UP0768 - WELD #2 Copper Rich High Build Primer - 450ml aerosol

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064
Tel: (800) 340 7824; Fax: (800) 787 5150
Email: sales-us@u-pol.com Website: www.u-pol.com