

2306

Fibre Glast Developments Corporation
 385 Carr Drive
 Brookville, Ohio 45309
 Phone: 800.214.8572
 Fax: 937.833.6555
 www.fibreglast.com

Duratec® Reducer



Description

Enhance the flow and leveling properties of #1041 Duratec® Gray Surfacing Primer. This thinner reduces orange peel and porosity while allowing for a smoother spray flow.

Usage

For use with all Duratec® products requiring thinning prior to use.

Features

Duratec® Reducer enhances the flow and leveling properties of Duratec® primers and hi-gloss coatings. The end result is reduced porosity and orange peel.

Safety & Handling

Duratec® Reducer is extremely flammable. Do not apply near sparks, open flames or heat. Keep area ventilated. Do not smoke. Avoid continuous breathing of vapor. Duratec® Reducer contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Individuals should wash with soap and water before eating or drinking. All containers should be properly labeled to prevent accidental ingestion or improper disposal. Individuals should reseal any partly used material back in the container. Store under cool, dry conditions and away from open flames and high temperatures. For more detailed instructions on handling and storage, please see MSDS Sheets.

Product Properties	
Paint Related Material	UN1263
Flash Point	21 °F
Specific Gravity	0.797 gm/cc @ 20°C
Weight per Gallon	6.65 lbs
Evaporation Rate	>1 (n-butyl acetate = 1)
Vapor Pressure	41.3 mm hg
Duratec® Reducer Additive for Duratec® Gray Surfacing Primer	
Duratec Reducer Suggested	5-15% after catalyzing

*All properties are based on temperatures of 77°F (25°C)