

# 5028

**Fibre Glast Developments Corporation**  
 385 Carr Drive  
 Brookville, Ohio 45309  
 Phone: 800.214.8572  
 Fax: 937.833.6555  
 www.fibreglast.com

## ChromaGlast™ Exempt Solvent

CHROMAGLAST™  
 COATINGS BY 



The #5028 Solvent is the best option for reducing any of the ChromaGlast™ paints, primers sealers, and primer surfacers. Our high quality solvent is designed to be compliant for use in our low VOC paint with its exempt formula. Using this specialty slow-flash solvent will reduce paint-finish errors like orange peeling and pin holes.

ChromaGlast™ exempt solvent reduces the coatings for better spray-ability. The pure formula uses no water as filler to ensure a pure mix and consistency to reduce any coating imperfections. We package this solvent in a resealable metal container for shelf-stable storage.

Product Properties @ 70°F Ambient	
Physical State	Clear Liquid
Relative Density	1.34 (11.18 lbs/gal)
Boiling Point	>37.78°C (>100°F)
Flash Point	Closed cup: 42.78°C (109°F)
Kinematic Viscosity	>0.21 cm <sup>2</sup> /s (104°F)
VOC	0 (Exempt)
Container Contents	32 oz
Container Net Weight	2.75 lbs

### Mixing Ratios: Single Stage Paints

(by volume)

ChromaGlast #5027 Paint	Paint #5025 Hardener	Drying #5028 Accelerator	Exempt Solvent			
3	:	1	:	0.188	:	Up to 10%

### High Solids Primer Surfacer/Sealer

#5060/5062/5064 Paint	#5061 Hardener	#5028 Exempt Solvent		
3	:	1	:	10-15%

### Gray Epoxy Primer Sealer

#5052 Gray Paint	#5053 Hardener	#5028 Exempt Solvent		
3	:	1	:	1

### Application Notes

*Exempt Solvent is compatible with ChromaGlast™ paints and undercoats.*

*Be sure to review the allowable ratios for each product.*